



The article is no longer in our assortment.

Features:

ALUTRUSS Base Plate BP-30 80x80

Baseplate for mobile use (connectors 6082 included)

- For the vertical installation of truss elements
- Multifunctional use
- High durability
- Trusspipe: 50 mm
- Made in Europe
- For application areas such as: Trade fair and shop fitting; Wedding/gala/events

Logistic

ALUTRUSS QUADLOCK 6082-2000 4-Way Cross Beam

4-point truss system

- Strong EN-AW 6082 alloy for high loads
- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- Distance center - center: 240 mm
- Easy installation
- Trusspipe: 50 mm
- TÜV Süd certified
- For application areas such as: Theater; Trade fair and shop fitting; Clubs/dancing school
- For further information about this product, please refer to the Data Sheet under "Downloads"

Package contents

- 1 x connection Set

ALUTRUSS QUADLOCK End Plate QQGP

Robust truss system

- High stability
- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- Easy installation as the cross-beams do no longer need to be screwed on
- Easy installation
- Trusspipe: 50 mm
- Made in Europe
- For application areas such as: Theater; Trade fair and shop fitting; Clubs/dancing school

ALUTRUSS QUADLOCK set connecting cone/pivot/pin

QUADSYSTEM set

- Accessories for the robust truss system
- Trusspipe: 50 mm
- Made in Europe

EUROLITE CRT-120 LED-Curtain

LED curtain with 120 LEDs RGB+yellow and compatible DMX controller (3 x 2 m)

- Several curtains can be linked via DMX512
- 120 powerful LEDs 5 mm R/G/B/A
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; Sound to light via Microphone
- Easy installation
- B1 low flammability
- For application areas such as: Party room; mobile djs / entertainer
- Water repellent
- Dimmer electronic; color selection manual; color change adjustable; color fade adjustable
- Strobe effect

Package contents

- 1 x controller, 1 x curtain, 1 x user manual, 1 x power cord, 58 x mounting material, 8 x illuminant

ALUTRUSS SINGLELOCK POWER PSP-3000 QUICK-LOCK Pipe

Single tube with quick-lock

- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- For decoration or frame construction for projection foils
- Easy installation
- Trusspipe: 50 mm
- Made in Europe
- For application areas such as: Trade fair construction; Stage; Rental

Package contents

- 1 x connection Set

EUROLITE TPC-56 Coupler Cone silver

Coupler for 50 mm tube with Quicklock 6082 conical connector, maximum load WLL 500 kg

- With conical connector matching the Quicklock truss systems Singlelock, Bilock, Trilock 6082, Quadlock 6082

Technical specifications:

Weight: 94,28 kg

Legal specifications

Special product: Not designed for household room illumination

Intended use: Show effect lighting

ALUTRUSS Base Plate BP-30 80x80

Trusspipe: 50 mm

Material: Steel

Color: Alu colored

Dimensions: Width: 80 cm
Depth: 80 cm
Height: 6 mm

Weight: 28,60 kg

ALUTRUSS QUADLOCK 6082-2000 4-Way Cross Beam

Setup: Easy installation

Trusspipe: 50 mm x 2 mm

Welding technique: TIG-welding

Welding material: AlMg 5

Alloy: AlMgSi1 T6

Color: Alu colored

Strut diameter x thickness: 16 x 2mm

Dimensions: Length: 2 m
Width: 29 cm
Height: 29 cm

Weight: 10,80 kg

ALUTRUSS QUADLOCK End Plate QQGP

Setup: Easy installation

Trusspipe: 50 mm

Color: Alu colored

Weight: 2,05 kg

ALUTRUSS QUADLOCK set connecting cone/pivot/pin

Trusspipe: 50 mm

Color: Alu colored

Weight: 960 g

EUROLITE CRT-120 LED-Curtain

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 15,00 W

IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
LED:	120 x 5 mm R/G/B/A
Flash rate:	1 - 12 Hz
DMX channels:	8
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; Sound to light via Microphone
Setup:	Easy installation
Housing color:	Black
Material:	, water repellent
Controller	
Dimensions:	Width: 18 cm Depth: 19 cm Height: 9 cm
Weight:	1,2 kg
Curtain	
Dimensions:	Width: 3 m Height: 2 m
Weight:	3,6 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ALUTRUSS SINGLELOCK POWER PSP-3000 QUICK-LOCK Pipe

Setup:	Easy installation
Trusspipe:	50 mm x 3 mm
Welding technique:	TIG-welding
Welding material:	AlMg 5
Alloy:	AlMgSi 0.5
Color:	Alu colored
Dimensions:	Length: 3 m
Weight:	3,95 kg

EUROLITE TPC-56 Coupler Cone silver

Maximum load BGV C1 (8-fold):	250 kg
Max. load WLL (4-fold):	500 kg
Tube diameter sector:	45 - 50 mm
Material:	Aluminum
Color:	Silver

Dimensions:

Length: 13 cm

Width: 5 cm

Depth: 11,50 cm

Weight:

610 g
