



The article is no longer in our assortment.

Features:

EUROLITE PAR-56 Spot Long With PAR-Safe sil

Classic spotlight

- Rugged metal housing
- Heat-resistant fixing screw
- The screw is protected against turning it too far out
- If the screw is loosened the spot remains in its position due to the brake
- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Safety grille (splinter protection) is integrated in the tube
- Blackened tube for precise light output
- Strong extension spring for safe hold and for quick opening of the rear housing cover
- Strong cable tension relief
- With Mounting bracket
- For PAR 56

Package contents

- 1 x spotlight, 1 x filter frame, 1 x lamp clamping ring, 1 x user manual

OMNILUX PAR-56 230V/300W NSP 2000h H

Special lamp for show effect lighting

- Dimmable
- Hot restrike
- Very high color rendering index (CRI)

Logistic

Technical specifications:

| | |
|----------------------|--|
| Weight: | 2,04 kg |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

EUROLITE PAR-56 Spot Long With PAR-Safe sil

| | |
|----------------------|--|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | Max. 500 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Fixed Supply cord with open wires |
| Base: | GX16d |
| Lamp type: | Selectable |
| Color generation: | Via color filter frame (optional) |
| Housing color: | Silver |
| Attachment system: | Mounting bracket |
| Color: | Black |
| Dimensions: | Width: 35 cm Depth: 25 cm Height: 30 cm |
| Weight: | 1,48 kg |
| Filter frame | |
| Dimensions: | Length: 22,5 cm Width: 22,5 cm Diameter: Ø 17,6 cm |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

OMNILUX PAR-56 230V/300W NSP 2000h H

| | |
|---------------------|--|
| Operating voltage: | 230 V, 220 - 240 V |
| Nominal wattage: | 300 W |
| Base: | GX16d |
| Lamp type: | Halogen lamp; clear lamp; high voltage lamp; sealed beam lamp; halogen bulb |
| Lamp specification: | Dimmable Hot restrike |
| Beam angle: | 10° |
| Color of light: | White |

| | |
|------------------------------|------------------|
| Color temperature: | 2750K |
| Color rendering index (CRI): | 95 Ra |
| Lead time: | 0 s |
| Construction: | PAR-56 |
| Operating temperature max.: | 40° C |
| Operating temperature min.: | 20° C |
| Burning position: | S180 (universal) |
| Lamp life: | 2000 h |
| Luminous flux: | 3500 lm |
| Dimensions (LxD): | 127x178 mm |
| Weight: | 560 g |