



The article is no longer in our assortment.

Features:

EUROLITE PAR-56 Spot Short with Cable sil

PAR-56 housing with silicone cable and open cable ends

- Heat-resistant fixing screw
- The screw is protected against turning it too far out
- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Strong cable tension relief
- The device is cooled by passive convection cooling
- With Mounting bracket
- For PAR 56

Package contents

- 1 x spotlight, 1 x filter frame, 1 x lamp clamping ring, 1 x user manual

Logistic

EUROLITE Raylight PAR-56,GY-9.5 Socket long

The alternative to traditional lamps

- Immediately and without changing the wiring, exchangeable by flanged on pin socket (GX 16) against a PAR-56 lamp
- Cost savings, as only the burner must be replaced at a lamp change
- Longlife lamp types (up to 2.000 h) also save time and money
- Low weight

GE M38 240V/300W GY-9.5 2000h

Studio-lamp for base GY9.5

- One-sided base

- Dimmable
- Hot restrike
- Very high color rendering index (CRI)
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

| | |
|----------------------|--|
| Weight: | 940 g |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

EUROLITE PAR-56 Spot Short with Cable sil

| | |
|--------------------------|--|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | Max. 500 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Suitable lamp: | Max. 230 V/500 W PAR-56 |
| Power connection: | Fixed Supply cord with open wires |
| Cable construction: | 3 x 0,75 mm ² H05SS-F |
| Cable length: | Approx. 0,8 m |
| Base: | GX16d |
| Lamp type: | Selectable |
| Color generation: | Via color filter frame |
| Cooling: | Passive convection cooling |
| Housing color: | Silver |
| Attachment system: | Mounting bracket |
| Material: | Aluminum |
| Slot for spot length: | 21,4 cm x 21,8 cm |
| Dimensions: | Length: 26 cm Width: 23,5 cm Height: 22 cm |
| Weight: | 800 g |
| Mounting bracket | |
| Diameter mounting holes: | 2 x Ø13mm |
| Material: | Metal, 2 mm |
| Filter frame | |
| Diameter mounting holes: | 4 x Ø8mm |
| Shape: | Octagonal |
| Grid size: | 10 x 10 mm |
| Material: | Aluminum, 0,6 mm |
| Dimensions: | Length: 21,5 cm Width: 21,5 cm |

Diameter: Ø 17,1 cm

Lamp clamping ring

Material: Steel, 4 mm

Color: Silver

Legal specifications

Special product: Not designed for household room illumination

Intended use: Show effect lighting

EUROLITE Raylight PAR-56,GY-9.5 Socket long

Power supply: 230 V AC, 50 Hz

Power consumption: 500 W

Base: GY9.5; GX16d

Beam angle (1/2 peak): NSP

Color: Alu colored

Dimensions: Diameter: Ø 17,5 cm

Weight: 120 g

GE M38 240V/300W GY-9.5 2000h

Operating voltage: 240 V, 220 - 240 V

Nominal wattage: 300 W

Base: GY9.5

Lamp type: Halogen lamp; clear lamp; high voltage lamp;
halogen bulb

Lamp specification: Dimmable
Hot restrike

Beam angle: 310°

Color of light: White

Color temperature: 2900K

Color rendering index (CRI): 100 Ra

Construction: Bi pin

Operating temperature max.: 40° C

Operating temperature min.: 10° C

Burning position: S180 (universal)

Lamp life: 2000 h

Luminous flux: 5500 lm

Dimensions (LxD): 80x29 mm

Weight: 20 g

Legal specifications

Special product: Not designed for household room illumination

Intended use: Show effect lighting
