



**The article is no longer in our assortment.**

### Features:

#### FUTURELIGHT DMH-32 RGBW LED Moving Head

LED Moving Head with one 32 W RGBW LED (4in1) and unique color effect prism

- Equipped with one 32 W quadcolor LED with RGBW colors
- Comparable to the light output of a 150 W discharge lamp
- Color effect prism: Not only the gobos, also the colors are split
- High PAN/TILT speed
- 16, 18 or 23 DMX channels selectable
- 5-facet prism
- Masterdimmer
- Color presets
- Stepless RGBW color changing
- Gobo wheel with 6 rotating gobos plus open
- All gobos can be interchanged
- With gobo shake function
- Exact positioning via 16 bit PAN/TILT movement resolution, dimmer intensity, colors
- Manual focus
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- Sound-controlled via built-in microphone
- Switch-mode power supply, automatic power supply adaption between 100 and 240 Volts without power selector
- Control board with graphic LCD and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset
- DMX-controlled operation or stand-alone operation with Master/Slave function

### Logistic

- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After 8 devices the fixtures must have a renewed connection with the power mains
- DMX control via any standard DMX controller
- Control via Sound to light via Microphone; RDM
- Preprogrammed in LED PC-Control 512

### EUROLITE DMX Move Controller 512

Controller with color & motion effects (28 devices, 18 control channels each)

- DMX controller for DMX light effect units such as moving heads, scanners and LED spot lights with RGBW color mixture
- 512 DMX channels can be assigned and inverted as desired to 32 control channels (softpatch)
- For 28 fixtures with 18 control channels each
- USB port for storing program data
- Quick programming thanks to 9 integrated movement patterns and 7 color effects (PAN/TILT position, fade time and running time adjustable)
- Manual, time-controlled or sound-controlled chase running mode
- 2 DMX fixture levels can be controlled, each with up to 18 channels
- 16 DMX channel faders
- 2 jog wheels for pan/tilt
- Blackout function
- Programmable 32 scenes/chases each with 600 cues )
- Can transmit up to 512 DMX channels
- Control via DMX; RDM
- Monochrome LCD display
- Firmware can be updated
- (19") 48.3 cm rack installation 3 U
- Desktop console housing
- For application areas such as: Clubs/dancing school; Stage; mobile djs / entertainer
- Silent operation

#### Package contents

- 1 x controller, 1 x user manual, 1 x external mains adapter

### Technical specifications:

---

#### Legal specifications

Special product: Not designed for household room illumination

Intended use: Show effect lighting

---

### FUTURELIGHT DMH-32 RGBW LED Moving Head

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 60 W

Max. TILT movement: 270° Positioning

Max. PAN movement: 630° Positioning

Gobos: Outside diameter 24mm  
Image diameter 19mm

DMX channels: 16

Control: Sound to light via Microphone; RDM

Preprogrammed in: LED PC-Control 512

---

Beam angle (1/2 peak):	12°
Color:	Black
Dimensions:	Width: 24,4 cm Depth: 20,8 cm Height: 34 cm
Weight:	7,40 kg
DMX channels:	16/18/23
DMX connection:	5-pin XLR
Sound-control:	via built-in microphone
LED type:	32 W QCL
LED number:	1
Beam angle:	12°
Rotating gobo-wheel:	6 gobos and open
Outside diameter of the gobos:	24 mm
Image diameter of the gobos:	19 mm
Maximum PAN-movement:	630°
Maximum TILT-movement:	270°
Dimensions (L x W x H):	244 x 208 x 340 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **EUROLITE DMX Move Controller 512**

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	2,70 W
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Mains input via Coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Programs:	Programmable 32 scenes/chases each with 600 cues )
DMX channels:	Output 512
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; RDM
Housing color:	Black
Display type:	Monochrome LCD display
Available storage media:	USB devices (FAT 32)
USB port:	Typ A
PC connect:	, firmware can be updated
Housing design:	(19") 48.3 cm rack installation 3 U Desktop console housing
Dimensions:	Width: 48,3 cm Depth: 13 cm Height: 8,9 cm

Weight:	2,39 kg
Noise classification:	Class 0 (no noise at all)