



**The article is no longer in our assortment.**

### Features:

#### EUROLITE Raylight PAR-64,GY-9.5 Socket long

The alternative to traditional lamps

- Immediately and without changing the wiring, exchangeable by flanged on pin socket (GX 16) against a PAR-64 lamp
- Cost savings, as only the burner must be replaced at a lamp change
- Longlife lamp types (up to 2.000 h) also save time and money
- Low weight

#### EUROLITE PAR-64 Spot Long with Cable sil

Long PAR-64 housing (with open cable ends)

- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Safety grille (splinter protection) is integrated in the tube
- Strong clamps with extension springs for safe hold and for quick opening of the rear housing cover
- Blackened tube for precise light output
- Strong cable tension relief
- With Mounting bracket
- Available in various colors
- For PAR 64
- For application areas such as: Advertisement/Shop window; Decoration; Clubs/dancing school

#### Package contents

- 1 x spotlight, 1 x filter frame, 1 x lamp clamping ring, 1 x user manual

### Logistic

## OMNILUX A1 230V/500W GY-9.5 75h

Special lamp for show effect lighting

- One-sided base
- Easy lamp replacement
- Dimmable
- Hot restrike
- Very high color rendering index (CRI)

### Technical specifications:

---

|                      |  |
|----------------------|--|
| Weight:              | 1,80 kg                                      |
| Legal specifications |  |
| Special product:     | Not designed for household room illumination |
| Intended use:        | Show effect lighting                         |

## EUROLITE Raylight PAR-64,GY-9.5 Socket long

|                        |                     |
|------------------------|---------------------|
| Power supply:          | 230 V AC, 50 Hz     |
| Power consumption:     | 500 W               |
| Base:                  | GY9.5; GX16d        |
| Beam angle (1/2 peak): | NSP                 |
| Color:                 | Alu colored         |
| Dimensions:            | Diameter: Ø 20,3 cm |
| Weight:                | 140 g               |

## EUROLITE PAR-64 Spot Long with Cable sil

|                       |  |
|-----------------------|--|
| Power supply:         | 230 V AC, 50 Hz                                      |
| Power consumption:    | Max. 1000 W  |
| IP classification:    | IP20   |
| Protection class:     | Protection class I                                   |
| Power connection:     | Fixed Supply cord with open wires                    |
| Cable length:         | Approx. 0,7 m  |
| Base:                 | GX16d  |
| Lamp type:            | Selectable   |
| Color generation:     | Via color filter frame (optional)                    |
| Housing color:        | Silver   |
| Attachment system:    | Mounting bracket                                     |
| Slot for spot length: | 25,7 cm x 25,7 cm                                    |
| Dimensions:           | Length: 41,5 cm<br>Width: 26,5 cm<br>Height: 34,5 cm |
| Weight:               | 1,63 kg  |

---

**Filter frame**

---

|             |  |
|-------------|--|
| Dimensions: | Length: 25,5 cm<br>Width: 25,5 cm<br>Diameter: Ø 20,2 cm |
|-------------|--|

---

**Legal specifications**

---

|                  |  |
|------------------|--|
| Special product: | Not designed for household room illumination |
| Intended use:    | Show effect lighting                         |

---

**OMNILUX A1 230V/500W GY-9.5 75h**

|                              |  |
|------------------------------|--|
| Operating voltage:           | 230 V, 220 - 240 V   |
| Nominal wattage:             | 500 W  |
| Base:                        | GY9.5  |
| Lamp type:                   | Halogen lamp; clear lamp; high voltage lamp;<br>halogen bulb |
| Lamp specification:          | Dimmable<br>Hot restrike                                     |
| Beam angle:                  | 310°   |
| Color of light:              | White  |
| Color temperature:           | 3200K  |
| Color rendering index (CRI): | 95 Ra  |
| Lead time:                   | 0 s  |
| Construction:                | Bi pin   |
| Operating temperature max.:  | 40° C  |
| Operating temperature min.:  | 20° C  |
| Burning position:            | S180 (universal)   |
| Lamp life:                   | 75 h   |
| Luminous flux:               | 7200 lm  |
| Weight:                      | 20 g   |

---

**Legal specifications**

---

|                  |  |
|------------------|--|
| Special product: | Not designed for household room illumination |
| Intended use:    | Show effect lighting                         |

---