



The article is no longer in our assortment.

Features:

Logistic

EUROLITE T-36 Pinspot with Cable, black

Pinspot for PAR-36 6 V/30 W lamp

- At a distance of 4 m there is projected a light circle with a diameter of 30 cm
- Separately capsuled transformer chamber
- Color caps or color foils can be attached in front of the lens
- For illuminating e.g. mirror balls, entrance or counter areas or as basic illumination
- Interesting price levels for purchase of larger quantities
- Low power consumption
- Control via plug and play
- With Mounting bracket
- Various versions available

Package contents

- 1 x spotlight, 1 x lamp clamping ring, 1 x user manual

OMNILUX PAR-36 6.4V/30W G-53 VN5P 200h

PAR-36 lamp

- Harmless for color-foils
- The heat permeates the front-glass continuously
- Dimmable
- Hot restrike
- Very high color rendering index (CRI)
- For application areas such as: Clubs/dancing school; Stage

Technical specifications:

Weight:	14,56 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE T-36 Pinspot with Cable, black

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 30 W
IP classification:	IP20
Protection class:	Protection class I
Suitable lamp:	Max. 6,4 V/30 W PAR-36 G-53 STC
Power connection:	Fixed Supply cord with open wires
Cable construction:	3 x 0,75 mm ² H05VV-F
Cable length:	Approx. 0,9 m
Base:	Wires
Control:	Plug and play
Housing color:	Black matte
Attachment system:	Mounting bracket
Material:	Metal
Dimensions:	Length: 16 cm Width: 15,5 cm Height: 17 cm
Weight:	1,00 kg
Mounting bracket	
Diameter mounting holes:	3 x Ø10mm; 1 x Ø8mm
Material:	Metal, 2 mm
Lamp clamping ring	
Material:	Metal
Color:	Silver
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OMNILUX PAR-36 6.4V/30W G-53 VN5P 200h

Voltage (lamps):	6,4 V
Nominal wattage:	30 W
Base:	G-53 STC

Lamp type:	Halogen lamp; clear lamp; low voltage lamp; sealed beam lamp; halogen bulb
Lamp specification:	Dimmable Hot restrike
Beam angle:	6°
Color of light:	Warm white WW <3300 K
Color rendering index (CRI):	95 Ra
Lead time:	0 s
Construction:	PAR-36
Operating temperature max.:	+40° C
Operating temperature min.:	-20° C
Burning position:	S180 (universal)
Lamp life:	200 h
Luminous flux:	510 lm
Dimensions (LxD):	70x114 mm
Weight:	210 g
Energy efficiency class (A - G):	G