

OMNITRONIC RS-602 Recording Mixer

Compact 6-channel studio and live mixer

Art. No.: 10040050

GTIN: 4026397183238



The article is no longer in our assortment.

Features:

- Low-noise 6-channel mic/line mixer
- 2 mono inputs with XLR sockets, +48V phantom power and balanced line inputs
- 2 stereo inputs with balanced 6.3 mm jack sockets
- Stereo inputs can also be operated mono
- 3-band EQ for all inputs
- Peak LED per mono input
- Aux send per channel for controlling external effectors
- Stereo aux return with balanced 6.3 mm jack sockets
- Separate main mix, booth and headphones outputs
- Tape inputs assignable to master, booth/headphones
- Precise 10-fold stereo LED meter

Logistic

EAN / GTIN: 4026397183238

Weight: 2,90 kg

Length: 0.32 m

Width: 0.30 m

Height: 0.12 m

Technical specifications:

| | |
|--------------------|--|
| Power consumption: | 15,00 W |
| Dimensions: | Width: 22 cm Depth: 25 cm Height: 5,5 cm |
| Weight: | 2,40 kg |
| Power supply: | 2 x 20 V AC, 50/60 Hz via included power unit |
| Inputs: | |

| | |
|-------------------------|-----------------------------|
| 2 x mono | XLR or balanced 6.3 mm jack |
| 2 x stereo | balanced 6.3 mm jacks |
| 1 x Aux Return: | balanced 6.3 mm jacks |
| 1 x Tape In | stereo RCA |
| Outputs: | |
| 1 x Master Out | balanced 6.3 mm jacks |
| 1 x Control Room | balanced 6.3 mm jacks |
| 1 x Aux Send: | balanced 6.3 mm jacks |
| 1 x Tape Out | stereo RCA |
| Frequency range: | |
| Microphone: | 10-60000 Hz, ± 3 dB |
| Mono: | 10-60000 Hz, ± 3 dB |
| Stereo: | 10-55000 Hz, ± 3 dB |
| Distortion: | 0.01 % |
| S/N ratio: | 112 dB |
| Tone control/channel: | |
| Treble: | ± 15 dB at 12 kHz |
| Middle: | ± 15 dB at 2.5 kHz |
| Bass: | ± 15 dB at 80 Hz |
| Dimensions (W x D x H): | 220 x 250 x 55 mm |