

OMNITRONIC CS-816 Powered Mixer

Universal powered stage mixer with DSP effects unit

Art. No.: 10050200

GTIN: 4026397230840



The article is no longer in our assortment.

Features:

- Low-noise 12-channel mic/line mixer and amplifier with 2 x 350 W/4 ohms output power
- Integrated DSP effect unit with LED display 256 effects
- 8 mono input channels (XLR and 6.3 mm jack) with gain control, 3-band EQ, pan and effect control
- Insert or direct out (6.3 mm jack) per mono channel
- 2 stereo input channels (6.3 mm jack)
- Aux send per channel for controlling external effectors
- Adjustable aux return input (6.3 mm jack)
- 2 adjustable CD inputs (stereo RCA) with crossfader
- Tape output (stereo RCA)
- +48V phantom power, can be switched centrally
- Precise 10-fold stereo LED meter
- 2 Speaker outputs

Logistic

EAN / GTIN: 4026397230840

Weight: 17,00 kg

Length: 0.42 m

Width: 0.42 m

Height: 0.64 m

Technical specifications:

| | |
|--------------------|--------------------------------------|
| Power supply: | 115/230 V AC, 50/60 Hz |
| Power consumption: | 1250,00 W |
| Output power: | Max. 700 W 350 W RMS (4 ohms) |
| Circuitry: | Class AB |
| Equalizer: | Master: 2 x Graphic equalizer 7-band |

| | |
|-------------------------|---|
| Dimensions: | Width: 54 cm Depth: 33 cm Height: 32 cm |
| Weight: | 14 kg |
| Inputs: | |
| 8 mono | XLR or balanced 6.3 mm jacks |
| 8 inserts | balanced 6.3 mm jacks |
| 2 stereo | balanced 6.3 mm jacks |
| 1 aux return | balanced 6.3 mm jacks |
| 2 CD | RCA |
| Outputs: | |
| 2 master | Speaker sockets |
| 1 aux send | balanced 6.3 mm jacks |
| 8 insert | balanced 6.3 mm jacks |
| 1 Tape | RCA |
| Frequency range: | |
| Microphone: | 10-60000 Hz, ± 3 dB |
| Mono: | 10-60000 Hz, ± 3 dB |
| Stereo: | 10-55000 Hz, ± 3 dB |
| Distortion: | 0.01 % |
| S/N ratio: | 112 dB |
| Tone control/channel: | |
| Treble: | ± 15 dB at 12 kHz |
| Middle: | ± 15 dB at 2.5 kHz |
| Bass: | ± 15 dB at 80 Hz |
| Power output sine: | |
| Stereo 4 ohms: | 2 x 350 W |
| Dimensions (W x D x H): | 540 x 330 x 320 mm |