

OMNITRONIC LS-622A Powered Live Mixer

6-channel powered live mixer with 2 x 150 W/4 ohms

Art. No.: 10060050

GTIN: 4026397183306



Features:

- Low-noise 6-channel Mic/Line mixer
- 2 mono inputs with XLR sockets, +48V phantom power and balanced line inputs
- Insert or Direct Out for every mono channel
- 2 stereo inputs via balanced jacks
- Integrated effect unit with 9-level echo
- 3-band EQ for all inputs
- Peak LED per mono input
- Aux send per channel for controlling external effectors
- Aux return with balanced 6.3 mm jack socket
- Separate Main Mix, Group and headphones outputs
- Tape inputs and outputs
- 7-band equalizer for fine-tuned sound
- Precise 10-fold stereo LED meter
- Output power 2 x 150 W/4 ohms
- Digital signal processor

Logistic

EAN / GTIN: 4026397183306

Weight: 10,20 kg

Length: 0.47 m

Width: 0.43 m

Height: 0.24 m

Technical specifications:

| | |
|--------------------|----------------------------------|
| Power supply: | 115/230 V AC, 50/60 Hz |
| Power consumption: | 500.00 W |
| Output power: | Max. 300 W 150 W RMS (4 ohms) |

| | |
|-----------------------|--|
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Frequency range: | 10 - 60000 Hz microphone 10 - 60000 Hz mono 10 - 55000 Hz stereo |
| S/N ratio: | >112 dB |
| THD: | <0.01 % at 1 kHz |
| DSP: | Digital signal processor |
| Circuitry: | Class AB |
| Equalizer: | Master: 1 x graphic equalizer 7-band stereo |
| Dimensions: | Width: 33 cm Depth: 39 cm Height: 12.5 cm |
| Weight: | 8.40 kg |
| Inputs: | |
| 2 mono | XLR or balanced 6.3 mm jacks |
| 2 inserts | 6.3 mm jacks |
| 2 stereo | balanced 6.3 mm jacks |
| 1 Aux-Return | balanced 6.3 mm jacks |
| Tape In | RCA |
| Outputs: | |
| 1 Main Out: | XLR or balanced 6.3 mm jacks |
| 1 Headphone | balanced 6.3 mm jack |
| 1 Aux Send: | balanced 6.3 mm jack |
| 2 Direct Out | 6.3 mm jacks |
| Tape Out | RCA |
| Tone control/channel: | |
| Treble: | ±15 dB at 12 kHz |
| Middle: | ±15 dB at 2.5 kHz |
| Bass: | ±15 dB at 80 Hz |
| Power output sine: | |
| Stereo 4 ohms | 2 x 150 W |

Scope of delivery:
