

OMNITRONIC LH-070 Active dual DI box XLR

Dual DI box/splitter

Art. No.: 10355070

GTIN: 4026397194937



The article is no longer in our assortment.

Features:

- Active 2-channel DI box with split mode
- 2 high-impedance XLR signal inputs
- 2 low-impedance XLR outputs
- Switchable to split mode (input 1 routes the signal to both outputs)
- Input sensitivity switchable: +20 dB, 0 dB, -30 dB
- Ground-lift switch eliminates signal interference and ground loop problems
- Phase can be switched
- Hi-cut 10 kHz switchable
- Modern convex housing design with rubber corners for safe positioning
- Stackable
- Cables can be routed under the housing
- Operation with 9 V battery (included)

Logistic

EAN / GTIN: 4026397194937

Weight: 0,75 kg

Length: 0.23 m

Width: 0.16 m

Height: 0.10 m

Technical specifications:

| | |
|------------------|---|
| Battery: | 1 x 9.0 V E block 6LR61 alkaline manganese included |
| Frequency range: | 10 - 30000 Hz |
| Dimensions: | Width: 15 cm Depth: 13 cm Height: 6 cm |
| Weight: | 550 g |

| | |
|-----------------------|---------------|
| Power supply: | 9 V battery |
| Current consumption: | approx. 65 mA |
| Battery life: | 6-8 hours |
| Input impedance: | 470 kohms |
| Output impedance: | 600 ohms |
| Maximum output level: | 6 dBu |
| Dynamic range: | >100 dB |
| Hi cut: | 10 kHz |
| Input connectors: | 2 x XLR, bal. |
| Output connectors: | 2 x XLR, bal. |
| THD: | 0.5 % |