

OMNITRONIC XO-23S Active crossover

High-quality stereo crossover

Art. No.: 10355630

GTIN: 4026397393101











The article is no longer in our assortment.

Features:

- 2-way stereo operation / 3-way mono operation
- Additional Subwoofer output
- 24 dB octave slope
- Crossover frequency control on the front panel
- Frequency range of crossover frequency Low/High band 100 Hz to 7 kHz
- Frequency range of crossover frequency Subwoofer 50 Hz to 350 Hz
- Individual output level controls for all bands
- Low cut switch
- Phase invert control
- XLR inputs and outputs
- Illuminated switches for secure operation in dark environments
- Rack installation

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	10,00 W
Dimensions:	Width: 48,3 cm Depth: 14,7 cm Height: 4,45 cm
Weight:	2,15 kg
Slope:	24 dB / octave

Logistic

EAN / GTIN: 4026397393101

Weight: 2,50 kg Length: 0.54 m Width: 0.20 m Heigth: 0.07 m

Operation modes:	2-way stereo/mono
Input:	Mono/stereo
Input impedance:	10/20 kohms (unb./bal.)
Output:	Mono/stereo
Output impedance:	300/150 kohms (unb./bal.)
In/out connectors:	XLR
S/N ratio:	>100 dB
THD:	0.05%
Input gain:	-~ to +6 dB
Ouptut gain:	-~ to +12 dB
Low cut:	30 Hz, -3 dB
Phase adjustment:	0-180°
Dimensions (W x D x H):	483 x 147 x 46 mm