

# OMNITRONIC TRM-202MK3 2-Channel Rotary Mixer (25th Omnitronic anniversary edition)

2-channel rotary mixer with 3-band frequency isolator for DJs

GTIN: 4026397691634



**The article is no longer in our assortment.**

## Features:

- Classic rotary mixer with 2 input channels and integrated 3-band frequency isolator for DJs
- Gain control, 2-way equalizer (highs/lows) and phono/line switching per channel
- Dedicated boost and kill cut
- Kill cut feature allows DJs to completely remove low, mid and high frequencies for amazing mixing
- Vintage ALPS potentiometers (Blue Velvet RK27)
- High-grade components ensure long life and excellent sound quality
- DJ microphone input with separate level control
- Prefader listening to input channels and the master output via adjustable headphones output, with cue mix/split function
- 12-digit stereo LED level meter and master level control
- Booth output with separate level control
- Inputs: 4 x line and 2 x phono (RCA L/R), DJ microphone (XLR) and headphones (jack)
- Outputs: master and booth (XLR/RCA L/R), record (stereo RCA)
- Matching woodkits available at [www.omniwoodkit.com](http://www.omniwoodkit.com)
- Desktop console housing

## Logistic

EAN / GTIN: 4026397691634

Weight: 3,18 kg

Length: 0.14 m

Width: 0.25 m

Height: 0.32 m

## Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 20 W

Protection class: Protection class I

Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Frequency range:	20 - 20000 Hz Microphone 20 - 20000 Hz line 40 - 18000 Hz phono
S/N ratio:	>77 dB phono >80 dB Microphone >85 dB line
THD:	Line <0,03 % at 1 kHz Phono <0,1 % at 1 kHz
Gain:	Microphone 44 dB Line 20 dB Phono 60 dB to +75 dB
Isolators:	Master Gain: - ? bis +9 Low/mid 300 Hz, 18db/oct , Butterworth Mid/high 4000 Hz, 18db/oct , Butterworth
Control elements:	Power switch, source selector
Status LED:	Power, master level meter, chanal source, CUE, Microphone
Connections:	Input: line via 2 x stereo RCA Input: line/phono via 2 x stereo RCA Input: Microphone via 1 x 3-pin XLR Output: headphones via 1 x 6.3 mm jack socket (stereo) mounting version Output: rec. via 1 x stereo RCA Output: booth via 2 x 3-pin XLR Output: booth via 1 x stereo RCA Output: master via 2 x 3-pin XLR Output: master via 1 x stereo RCA
Channels:	Input chanel: 2 x stereo with Line-Line/Phono switch via RCA, channel control via Rotary, 2-band tone control EQ, Phono gain rotery, source selector, CUE switch  Microphon chanal: 1 x mono via XLR, channel control via Rotary dial  Booth output: 1 x stereo via XLR or RCA, channel control via Rotary dial  Master output: 1 x stereo via XLR or RCA, channel control via Rotary dial  Headphones output: 1 x stereo via Jack, channel control via Rotary dial
Max. level:	Output: +22 dBu
Housing design:	Desktop console housing
Dimensions:	Width: 19 cm Depth: 25 cm Height: 10,7 cm
Weight:	2,68 kg