

## OMNITRONIC TRM-222 2-channel Rotary Mixer

Rotary mixer with 3-band frequency isolator, VCR filter and FX loop

Art. No.: 10355932

GTIN: 4026397716375



### Features:

- Filter section with resonance and sweep control for creative sound shaping
- 3-band master frequency isolator with vintage ALPS potentiometers (Blue Velvet RK27)
- Kill cut feature allows DJs to completely remove low, mid and high frequencies for amazing mixing
- 2 stereo input channels with gain control, clip LED, 3-way equalizer, FX Send and phono/line switching
- 2 microphone input channels with gain control, 2-way equalizer on air switch
- 2 effects send/return paths
- Dual analog VU meter
- Direct outputs for Timecode applications
- High-grade components ensure long life and excellent sound quality
- Booth output with separate 2-way equalizer and level control
- Record output, independent of the master
- Fully assignable VCA crossfader with adjustable curve
- Outputs: master and booth (XLR/RCA L/R), record (RCA L/R), master insert send/return (RCA L/R), FX in/out (stereo jack)
- DJ filter LPF, HPF routable
- Desktop console housing
- For application areas such as: Clubs/dancing school; mobile use; mobile djs / entertainer; homerecording and studios

### Logistic

EAN / GTIN: 4026397716375

Weight: 7,10 kg

Length: 0.56 m

Width: 0.34 m

Height: 0.21 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

|                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power consumption: | 15 W                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Protection class:  | Protection class I                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Power connection:  | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Cable length:      | 1.5 m detachable                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Frequency range:   | 20 - 20000 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| S/N ratio:         | >100 dB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| THD:               | <0.05 % at 1 kHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Gain:              | Line -12 dB to +12 dB<br>Phono -40 dB to +5 dB<br>FX 20 dB<br>Microphone 55 dB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| DJ filter:         | Routable: LPF, HPF,                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Isolators:         | Master Gain:- ? bis +9<br>Low/mid 300 Hz, 18db/oct , Butterworth<br>Mid/high 4000 Hz, 18db/oct , Butterworth                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Housing color:     | Black; silver                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Control elements:  | Power switch, source selector, crossfader, crossfader selector switch, crossfade curve switch; cue mix split function, tone control                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Status LED:        | Power, master level meter, clip, CUE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Connections:       | Input: line via 2 x stereo RCA<br>Input: line/phono via 2 x stereo RCA<br>Input: microphone via 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version)<br>Input: AUX returns via 2 x 6.3-mm-jack (bal.)<br>Output: Timecode via 2 x stereo RCA<br>Output: headphones via 2 x 6.3 mm jack socket (stereo) mounting version<br>Output: headphones via 1 x 3.5 mm jack (stereo) mounting version<br>Output: rec. via 1 x stereo RCA<br>Output: booth via 2 x 3-pin XLR<br>Output: booth via 1 x stereo RCA<br>Output: master via 2 x 3-pin XLR<br>Output: master via 1 x stereo RCA<br>Output: AUX sends via 2 x 6.3-mm-jack (bal.)    |
| Channels:          | Input channel: 2 x stereo with line-line/phono switch via RCA, channel control via rotary, 3-band tone control EQ, source selector, gain control, CUE switch, FX routing switch<br><br>Microphone channel: 1 x mono via Combination socket (XLR/jack), channel control via rotary, 2-band tone control EQ, ON AIR switch<br><br>Master output: 1 x stereo via XLR or RCA, channel control via rotary<br><br>Booth output: 1 x stereo via XLR or RCA, channel control via rotary, 2-band tone control EQ<br><br>Rec. output: 1 x stereo via RCA, channel control via rotary<br><br>Headphones output: stereo via jack, channel control via rotary |
| Max. level:        | Output: +21 dBu                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Material:          | Metal; aluminum                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

|                 |                                               |
|-----------------|-----------------------------------------------|
| Housing design: | Desktop console housing                       |
| Dimensions:     | Width: 45 cm<br>Depth: 26 cm<br>Height: 16 cm |
| Weight:         | 5.80 kg                                       |

**Scope of delivery:**

- 1 x mixer
- 1 x power cord
- 1 x cover
- 1 x user manual