

OMNITRONIC FX-003 FX processor

Digital 24-Bit stereo multi-effects processor

Art. No.: 10356730

GTIN: 4026397306279



The article is no longer in our assortment.

Description:

That's the way I like it!

Amongst guitar players it is common practice and taken for granted on every stage or studio at home: effect gadgets. Whether wah-wah, chorus or flanger, via step on the effect pedals, a musician can shape the sound of his guitar with many variants. But this opportunity is not only given to guitarists. With the new OMNITRONIC FX-003 effect processor, DJs in studios or on live events can easily be compared to string acrobats. This gadget disposes over 16 impressive effect algorithms, for example: vocal remover, different reverbs and delays, chorus, flanger, rotary speaker as well as multi-effects. Via its control button - bright LEDs always display which effect is currently adjusted - it is operated by intuition and is providing the DJ with a tool which guarantees diversity and also gives the opportunity, to give the music a personal touch. Hereby, the two channel effect processor is with only one height unit exceptionally compact. A small device with a big effect which you should not miss out on.

Features:

- Compact 2-channel effects processor for studio and stage applications
- 16 striking effect algorithms, including vocal removal, various reverbs and delays, chorus, flanger rotary speaker and multi-effects
- Intuitive effects selector with LEDs indicating the selected effect
- Adjustable output level
- Inputs and outputs via balanced XLR connectors
- Optional mounting kit available for rack installation (1 U)

Logistic

EAN / GTIN: 4026397306279

Weight: 1,90 kg

Length: 0.32 m

Width: 0.20 m

Height: 0.08 m

Technical specifications:

| | |
|-------------------------|---|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | 10,00 W |
| Frequency range: | 20 - 20000 Hz |
| Dimensions: | Width: 19,6 cm Depth: 16,5 cm Height: 4,45 cm |
| Weight: | 1,50 kg |
| S/N ratio: | >90 dB |
| THD: | 0.05% |
| Crosstalk: | >80 dB, -3 dB |
| Gain: | -- to +6 dB |
| Input impedance: | 20 kohms |
| Output impedance: | 150 kohms |
| Connection: | XLR (bal.) |
| Dimensions (W x D x H): | 196 x 165 x 46 mm |
