

## OMNITRONIC XPA-2700 Amplifier

Class H PA amplifier with limiter, 2 x 1350 W RMS (4 ohms), 2 x 1080 W RMS (8 ohms)

Art. No.: 10451037

GTIN: 4026397593921



**List price: 653.31 €**

incl. 19% VAT.

### Features:

- 3 operating modes can be selected (stereo, parallel or bridged)
- Input sensitivity adjustable
- 2 level controls
- Each channel with LED for activated protective circuit (protect) and output meter with clip LED
- Signal inputs via XLR or RCA connectors
- Speaker outputs via lockable speaker jacks and pairs of screw terminals
- Class H circuitry
- The device is cooled by cooling fan
- (19") 48.3 cm rack installation 2 U
- For application areas such as: Clubs/dancing school; Installation; mobile use; mobile djs / entertainer; restaurants, bars and hotels; Rental; sports centres/gyms

#### Package contents

- 1 x amplifier, 1 x user manual, 1 x power cord, 4 x foot, 4 x screw

### Logistic

EAN / GTIN: 4026397593921

Weight: 17,00 kg

Length: 0.53 m

Width: 0.48 m

Height: 0.14 m

### Technical specifications:

|                    |   |
|--------------------|---|
| Power supply:      | 230 V AC, 50 Hz   |
| Power consumption: | 700 W 1/8 power   |
| Output power:      | 2 x 1350 W RMS (4 ohms)<br>2 x 1080 W RMS (8 ohms)<br>2700 W RMS bridged (8 ohms)               |
| Power connection:  | Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug (provided) |

|                    |  |
|--------------------|--|
| Frequency range:   | 20 - 20000 Hz  |
| S/N ratio:         | >100 dB  |
| THD:               | <0,5 % at 1 kHz  |
| Cooling:           | Cooling fan  |
| Impedance:         | Input: 20 kOhm , bal.<br>Input: 10 kOhm , unbal.   |
| Circuitry:         | Class H  |
| Slew rate:         | >10 V/ $\mu$ s   |
| Damping factor:    | >200   |
| Control elements:  | Power switch, level control per channel, mode switch (stereo/parallel/bridged), Input sensitivity switch   |
| Controls:          | Short-circuit; overheat; DC voltage; power on/off transients; softstart; power on/off transient  |
| Status LED:        | Power, level meter, clip, bridged, protect   |
| Connections:       | Input: line via 2 x 3-pin XLR<br>Input: line via 1 x stereo RCA<br>Output: speaker via 2 x speaker built-in socket (F)<br>Output: speaker via screw terminal |
| Input sensitivity: | 0,775 V; 1,4 V , switchable  |
| Housing design:    | (19") 48.3 cm rack installation 2 U  |
| Dimensions:        | Width: 48,3 cm<br>Depth: 41,5 cm<br>Height: 8,9 cm   |
| Weight:            | 15,70 kg   |