

## OMNITRONIC XDA-1206 6-Channel Class D Amplifier

Class D multi-channel PA amplifier with SMPS, 6 x 200 W RMS (4 ohms), 6 x 150 W RMS (8 ohms)

Art. No.: 10451638

GTIN: 4026397670752



**List price: 534.31 €**

incl. 19% VAT.

### Features:

- Extremely low weight and height due to integrated switch mode power supply
- Level control per channel
- (19") 48.3 cm rack installation 1 U
- For application areas such as: Clubs/dancing school; Installation; mobile use; mobile djs / entertainer; restaurants, bars and hotels; Rental; sports centres/gyms

#### Package contents

- 1 x amplifier, 1 x user manual, 1 x power cord, 6 x screw plug-in terminal, 4 x foot

### Logistic

EAN / GTIN: 4026397670752

Weight: 4,30 kg

Length: 0.52 m

Width: 0.29 m

Height: 0.13 m

### Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	1440 W
Protection class:	Protection class I
Output power:	6 x 200 W RMS (4 ohms) 6 x 150 W RMS (8 ohms)
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Frequency range:	20 - 20000 Hz
S/N ratio:	>100 dB
THD:	<0,05 % at 1 kHz
Impedance:	Input: 20 kOhm , bal.

	Input: 10 kOhm , unbal.
Circuitry:	Class D
Control elements:	Power switch, level control per channel
Controls:	Softstart; overheat; overload; short-circuit; DC voltage
Status LED:	Power, signal, clip
Connections:	Input: line via 6 x 3-pin XLR Input: 6 x screw plug-in terminal Link: line via 6 x screw plug-in terminal Output: speaker via 6 x screw plug-in terminal
Housing design:	(19") 48.3 cm rack installation 1 U
Dimensions:	Width: 48,3 cm Depth: 20,5 cm Height: 4,4 cm
Weight:	3,75 kg