

OMNITRONIC CDP-600 Double CD player

Tabletop dual CD player

Art. No.: 10602320 GTIN: 4026397188585











The article is no longer in our assortment.

Features:

- Realtime scratch function without delay and time limit
- Scratch wheel for scratching and adjusting the Pitch Bend or effect parameter
- 5 built-in sound effects: Brake Effect (immediate stop/brake of the track), Scratch, Flanger, Filter and unlimited reverse play
- Seamless Loop function via A button, B/Exit button and Reloop button
- Realtime Cue button for memorizing the Cue point during playback
- Speed control range adjustable to ±4 %, ±8 % or ±16 %
- Main tempo function
- Pitch adjustment via pitchfader is displayed (in % or BPM)
- Auto beatcounter
- With manual beatcounter for showing the bass beats in BPM
- Relay button for switching playback automatically to the other player after every track
- Comfortable track selection via Track buttons and +10 button
- Sequence search via Search buttons
- Framewise search (1/75 sec)
- Open/Close buttons locked in play mode
- Display switchable from track remain time to total remain time to track playback time
- The 2 x 10 second Anti-Shock buffer keeps the CD from jumping
- Digital output via RCA
- Exquisit design with anodized aluminum front panel
- Comfortable operation due to well-structured front panel design
- With illuminated CD tray
- LED display of all important functions
- For standard CDs (8 cm and 12 cm)
- Rack installation

Logistic

EAN / GTIN: 4026397188585

Weight: 10,00 kg Length: 0.54 m Width: 0.46 m Heigth: 0.23 m

Technical specifications:

Teermour speemeations.	
Power supply:	115/230 V AC, 50/60 Hz
Power consumption:	20,00 W
Dimensions:	Width: 48,3 cm
	Depth: 26,2 cm
	Height: 8,9 cm
Туре:	Dual Compact Disc Player
Available disc:	Standard CDs (8 and 12 cm)
Quantisation:	D/A converter: 1 bit
Sampler frequency:	44.1 kHz
Program memory:	Up to 20 songs
Frame accuracy:	1/75 sec
Pitch adjustment:	±8 %, ±12 %, ±16 %
Display:	Remaining track time and track playback time
Distortion:	0.02 %
S/N ratio:	75 dB
Channel seperation:	70 dB
Frequency range:	20-20000 Hz, ±1 dB
Audio output:	unbalanced via RCA
Output level:	1 Vrms
Digital ouput:	unbalanced via RCA
Dimensions:	482 x 88.8 x 262 mm (CD player)
	482 x 132 x 74 mm (control unit)
	Rack installation
Weight:	5 kg (CD player)
	1.9 kg (control unit)