

OMNITRONIC DD-4750 USB turntable

Direct drive DJ turntable with USB interface and recording software

Art. No.: 10603020

GTIN: 4026397356076



The article is no longer in our assortment.

Features:

- Direct drive high-torque motor
- Quartz-controlled for highest speed precision
- Built-in USB port and additional phono preamplifier, for a high-quality and convenient digitization of analog vinyl records
- Plug & play: no driver installation required, unit is identified automatically
- Sampling rates of 44.1 kHz and 48 kHz in stereo, resolution: 16 bits
- Incl. software for recording and editing
- 3 speeds (33 1/3, 45 and 78 RPM), pitch control $\pm 10\%$, $\pm 20\%$, $\pm 50\%$
- Quick start
- 2 large start/pause buttons
- Selectable quartz-controlled pitch lock
- Motor with reverse run can be switched off
- Plug-in LED target lamp
- Adjustable anti-skating
- Tone arm height adjustable
- Shock-absorbing feet
- Switchable phono/line output
- Delivery includes pick-up system, slipmat, RCA and USB cable
- USB 1.1 support
- Suitable for Windows XP, Vista, 7 and Mac OS X
- Delivery without dust cover

Logistic

EAN / GTIN: 4026397356076

Weight: 10,90 kg

Length: 0.52 m

Width: 0.43 m

Height: 0.20 m

Technical specifications:

| | |
|------------------------------|---|
| Power supply: | 115/230 V AC, 50/60 Hz |
| Power consumption: | 13,50 W |
| Frequency range: | 50 - 20000 Hz |
| Dimensions: | Width: 44,9 cm Depth: 37 cm Height: 14,5 cm |
| Weight: | 9,80 kg |
| Type: | manual turntable |
| Drive method: | quartz-controlled direct drive |
| Motor: | brushless DC motor |
| Turntable platter: | d=330 mm, aluminum diecast |
| Speed: | 33 1/3 RPM, 45 RPM and 78 RPM |
| Change time between speeds: | <0.3 sec |
| Initial torque: | >3.5 kg/cm |
| Start time: | <0.3 sec |
| Brake: | electronic brake |
| Stop time: | <0.3 sec |
| Pitch adjustment: | ±10 %, ±20 %, ±50 % |
| Wow and flutter: | <0.1 % |
| Rumble: | 55 dB DIN B |
| Tone arm: | S-shape with Cardan's suspension |
| Tone arm length: | 230 mm |
| Overhang: | 15 mm |
| Anti-skating range: | 0-4 g |
| Applicable cartridge weight: | 6-10 g |
| Stylus pressure range: | 3-4 g |
| Phono output level: | 1.5-3.6 mV/ 1 kHz 5 cm/sec |
| Line output level: | 90-216 mV/ 1 kHz 5 cm/sec |
| Channel separation: | >15 dB |
| Output connectors: | RCA, USB type B |
| Dimensions: | 449 x 370 x 145 mm |