

## OMNITRONIC OD-22 Wall Speaker 8Ohms black

Weather-proof 2,5" wall speaker (IP44) with mount, 20 W RMS

Art. No.: 11036906

GTIN: 4026397543506



**List price: 43.91 €**

incl. 19% VAT.

### Features:

- 8-ohm PA speaker system for general applications
- 2 x 6 cm full-range speaker (2 x 2.5")
- 3.5 x 6 cm passive membrane
- Durable mounting plate with joint for panning and tilting allows ceiling or wall installation in most varying angles
- With panning and tilting mounting bracket for ceiling or wall installation in most varying angles
- Black aluminum grille
- Scratchproof and shockproof
- Suitable for outdoor use IP44
- For application areas such as: Trade fair and shop fitting; restaurants, bars and hotels; product presentations and lectures

#### Package contents

- 1 x compact cabinet speaker, 1 x user manual, 1 x mounting material, 8 x screw

### Logistic

EAN / GTIN: 4026397543506

Weight: 1,07 kg

Length: 0.28 m

Width: 0.14 m

Height: 0.12 m

### Technical specifications:

|                    |                                |
|--------------------|--------------------------------|
| IP classification: | IP44                           |
| Power:             | Program: 40W<br>Rated: 20W RMS |
| Frequency range:   | 120 - 22000 Hz                 |
| Sensitivity:       | 88 dB                          |
| Max. SPL:          | 104 dB                         |

|                    |  |
|--------------------|--|
| Dispersion angle:  | 60° x 60°  |
| Impedance:         | 8 ohms   |
| Attachment system: | Panning and tilting mounting bracket for ceiling or wall installation in most varying angles |
| Connections:       | Speaker via Spring terminal  |
| Speaker:           | 2 x full range loudspeaker 2,5"<br>Basket material: Steel<br>Conematerial: Cardboard/paper   |
| Material:          | ABS Acrylonitrile butadiene styrene  |
| Color:             | Black, scratchproof and shockproof   |
| Dimensions:        | Width: 20,9 cm<br>Depth: 10,9 cm<br>Height: 11 cm  |
| Weight:            | 930 g  |