

OMNITRONIC OD-6A Wall Speaker active white 2x

Active 2-way speaker pair with mount, 6,5" woofers and 40 W RMS

Art. No.: 11036929 GTIN: 4026397543698











The article is no longer in our assortment.

Features:

- Dedicated PA speaker systems for fixed installations
- 2-way system with 16.5 cm woofer (6.5") and dome tweeter, magnetic shielding
- Class A/B circuitry: optimum sound and power at low weight and compact dimensions
- Separate controls for volume, high and low frequencies
- Each speaker system is equipped with an unbalanced RCA input and balanced spring terminals
- Additional 3.5 mm jack input, ideal for portable MP3 players
- Attractive plastic cabinet with metal grille
- Panning and tilting mounting bracket allows ceiling or wall installation in most varying angles
- Packed as a pair
- For indoor PA applications
- With panning and tilting mounting bracket for ceiling or wall installation in most varying angles

Logistic

EAN / GTIN: 4026397543698

Weight: 9,50 kg Length: 0.50 m Width: 0.23 m Heigth: 0.33 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with Euro plug (provided)
Power:	Program: 80W Rated: 40W RMS
Frequency range:	80 - 20000 Hz
Attachment system:	Panning and tilting mounting bracket for ceiling or wall installation in most varying angles

Speaker:	1 x woofer 6,5"
Type of speaker:	On-ceiling/on-wall speaker
Color:	White
Dimensions:	Width: 19,5 cm
	Depth: 19,5 cm
	Height: 30 cm
Weight:	8,90 kg
Circuitry:	class A/B
Components:	16.5 cm woofer (6.5"), 2.5 cm tweeter (1")
Connection:	RCA, unbal.
	3.5 mm jack, unbal.
	spring terminals, bal.
Sensitivity:	89 dB
Maximum SPL:	96 dB
Dispersion angle:	170° x 170°