

OMNITRONIC KPA-210A PA cabinet active

Active 2-way speaker-system

Art. No.: 11038712

GTIN: 4026397288179



The article is no longer in our assortment.

Features:

- XLR- and jack socket for direct connection with the signal source (line, mic)
- Line/Mic-pad for input-level adjustment
- Large mid-range horn with powerful driver
- Bi-amped for cristal clear playback
- Ideal as floor-monitor, standing, on a speaker-stand or on a wall-mounting
- Strong protective grille for perfect protection
- Scratch-resistant plastic housing
- Compact speaker-system for car transport
- Ideal for live music or discotheques

Logistic

EAN / GTIN: 4026397288179

Weight: 14,70 kg

Length: 0.41 m

Width: 0.38 m

Heigh: 0.63 m

Technical specifications:

| | |
|-------------------------|---|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | 200,00 W |
| Output power: | Max. 200 W |
| Frequency range: | 55 - 18000 Hz |
| Dimensions: | Width: 53 cm Depth: 31 cm Height: 34,5 cm |
| Weight: | 13,15 kg |
| Dimensions (H x W x D): | 530 x 310 x 345 mm |

Speaker-system:

| | |
|-----------------------|--------------------------------------|
| Rated power: | 120 W RMS |
| Program power: | 240 W |
| Components: | 25 cm woofer (10"), 2.5 cm horn (1") |
| Inputs: | XLR/jack |
| Dispersion angle: | 90° x 40° |
| Maximum SPL: | 114 dB |
| Impedance: | 8 ohms |
| LF-amplifier: | |
| Maximum power output: | 200 W / 4 ohms |
| Distortion: | 0.1 % |
| HF-amplifier: | |
| Maximum power output: | 40 W / 4 ohms |
| Distortion: | 0.1 % |