

OMNITRONIC COMPACT-100 1.1 Active system

Mobile and compact active PA system, 100 watts RMS

Art. No.: 11038830

GTIN: 4026397512939











The article is no longer in our assortment.

Features:

- Mobile column PA system with top speaker and active subwoofer with class D circuitry
- Ultra-compact, extremely light this system can be installed and setup in no time
- Ideal for DJs, entertainers, small bands and various kinds of mobile PA applications
- Dual class D amplifier (70 W + 30 W RMS)
- 25 cm subwoofer in bassreflex cabinet provides powerful, dry bass
- Top with 16.5 cm bass-midrange speakers and 2.5 cm driver system
- Passive 2-way crossover, PTC tweeter protection
- Balanced XLR/6.3 mm inputs and XLR parallel output
- Master and subwoofer level controls
- Lockable speaker connectors
- Complete protection set against short-circuit, overheat, overload and overcurrent
- Scratch-resistant lacquer surface and flange

Logistic

EAN / GTIN: 4026397512939

Weight: 31,90 kg Length: 0.56 m Width: 0.42 m Heigth: 0.79 m Bulky product

Technical specifications:

| Power supply: | 115/230 V AC, 50/60 Hz | |
|--------------------|------------------------|--|
| Power consumption: | 150,00 W | |
| Dimensions: | Width: 48,1 cm | |
| | Depth: 33,6 cm | |
| | Height: 39,1 cm | |
| Power output sine: | | |
| Subwoofer: | 70 W RMS | |

| Satellite speakers: | 30 W RMS |
|-------------------------|--|
| Components: | |
| Subwoofer: | 25 cm woofer (10") |
| Satellite speakers: | 16.5 cm woofer (6.5"), 2.5 cm tweeter (1") |
| Frequency range: | |
| Subwoofer: | 45-140 Hz |
| Satellite speakers: | 140-20000 Hz |
| Line input: | XLR/6.3 mm jack, bal. |
| Parallel output: | XLR |
| Protection circuits: | Short-circuit, overheat, overload, overcurrent |
| Dimensions (L x W x H): | |
| Subwoofer: | 81 x 336 x 391 mm |
| Satellite speaker: | 221 x 231 x 359 mm |
| Weight: | |
| Subwoofer: | 19 kg |
| Satellite speaker: | 6.6 kg |