

OMNITRONIC MAXX-1508DSP 2.1 Active System

Powerful active PA system with DSP, Bluetooth, 700 W (15" sub, 8" tops)

Art. No.: 11038832

GTIN:



List price: 950.81 €

incl. 19% VAT.

Description:

The MAXX-1508DSP is an active 2.1 PA system with 700 watts output power. It provides perfect sound and good level stability in various kinds of mobile PA applications.

The high-power 15" subwoofer with power-efficient Class D amplifier in a bass reflex cabinet delivers powerful, dry bass. The two satellite loudspeakers with 8" bass/midrange drivers and 1" compression drivers are equipped with a passive 2-way crossover including PTC tweeter protection and ensure a well-rounded sound experience.

Equipped with a DSP (digital signal processor) which enables convenient application presets for quick sound contouring, the MAXX-1508DSP offers combined XLR and 6.3 mm inputs with XLR parallel output (for linking additional systems), and an additional RCA input with level adjustment. Enjoy music wirelessly from your smartphone or any other Bluetooth device via the integrated Bluetooth audio receiver and charge them at the same time via the integrated powerbank.

The MAXX-1508DSP subwoofer's professional hardware includes a rugged multiplex/MDF enclosure, scratch-resistant lacquer, steel grille and ergonomically shaped handles. Swivel castors for easy transport are optionally available. Matching speaker stands, distance tubes, and stand forks are also available as accessories.

Features:

Powerful active PA system with DSP, Bluetooth, 700 W (15" sub, 8" tops)

- For application areas such as: Mobile use; mobile djs / entertainer; Rental

Package contents

Logistic

- 1 x bass, 2 x top, 1 x user manual, 1 x power cord, 2 x speaker cable, 1 x declaration of conformity, 1 x strap

OMNITRONIC MAXX-1508 2-Way Top 2x

2 x 8" passive full-range speaker, 150 W RMS

- 2-way bass-reflex system with 8" bass-midrange speaker and 1" compression driver
- Serve as a mobile 2.1 system together with the MAXX-1508 subwoofer
- With passive 2-way crossover, PTC tweeter protection
- Black metal grille with acoustic foam
- Application possibility: Standing; suspended; monitoring; on stand
- With rigging points
- Rugged carrying handle
- For application areas such as: Mobile use; mobile djs / entertainer; Rental

Package contents

- 2 x top, 2 x speaker cable

OMNITRONIC MAXX-1508DSP 2.1 Active Subwoofer

Powerful 15" active subwoofer with DSP and Bluetooth, 700 watts

- 15" subwoofer with Class D amplifier in bassreflex cabinet
- Amplifier power: 400 W RMS + 2 x 150 W RMS for two satellites
- Serves as a mobile 2.1 system together with MAXX-1508 2-way tops
- Balanced signal input XLR/6.3 mm jack L/R
- Additional stereo RCA input, with level switch
- Separate volume control for subwoofer and satellites
- Stereo/mono selection
- Digital signal processor
- Control via Bluetooth
- Wheels optional
- Black metal grille with acoustic foam
- Application possibility: Standing
- DSP presets: FLAT; DJ; LIVE
- For application areas such as: Mobile use; mobile djs / entertainer; Rental

Package contents

- 1 x bass, 1 x user manual, 1 x power cord, 1 x strap, 1 x declaration of conformity

Technical specifications:

Weight: 46,55 kg

OMNITRONIC MAXX-1508 2-Way Top 2x

| | |
|-------------------|--|
| Power: | Program: 300W Rated: 150W RMS |
| Frequency range: | 120 - 18000 Hz |
| Sensitivity: | 92 dB |
| Max. SPL: | 116 dB |
| Dispersion angle: | 90° x 60° |
| Impedance: | 4 ohms |
| Flying points: | 5 x M8 thread |
| Connections: | Input: speaker via 1 x speaker built-in socket (F) |
| Speaker: | 1 x woofer 8" 1 x compression tweeter highs 1" |

| | |
|------------------|---|
| Type of speaker: | Compact cabinet speaker |
| Carrying handle: | 1 pc/pcs |
| Material: | MDF (Medium-density fiberboard), 16 mm |
| Dimensions: | Width: 25,5 cm Depth: 24,1 cm Height: 42,1 cm |
| Weight: | 17,25 kg |

OMNITRONIC MAXX-1508DSP 2.1 Active Subwoofer

| | |
|-----------------------|--|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | 800 W |
| Power: | Rated: 400W RMS LF |
| Frequency range: | 35 - 120 Hz Bass |
| Sensitivity: | 95 dB |
| Max. SPL: | 120 dB |
| DSP: | Digital signal processor |
| DSP presets: | FLAT; DJ; LIVE |
| Control: | Bluetooth |
| Attachment system: | M20 thread |
| Circuitry: | Class D |
| Controls: | Limiter |
| Status LED: | Power, signal, limit, pairing, DSP presets |
| Connections: | Input: 1 x stereo RCA Input: line via 2 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Output: line via 2 x 3-pin XLR (M) mounting version Output: speaker via 2 x speaker built-in socket (F) |
| Input channels: | 1 x stereo via XLR or RCA or bluetooth, channel control via Rotary dial |
| Speaker: | 1 x woofer 15" with ferrit magnet |
| Type of speaker: | Subwoofer |
| Type of construction: | Vented |
| Transport aid: | Wheels optional |
| Material: | Birch multiplex, 16 mm; MDF (Medium-density fiberboard) |
| Color: | Black, textured coating, painted |
| Dimensions: | Width: 45,4 cm Depth: 57 cm Height: 53,4 cm |
| Weight: | 29,30 kg |