

OMNITRONIC AZX-112A PA Subwoofer active 300W

Active 12" PA bassreflex subwoofer, 300 W RMS

Art. No.: 11039038 GTIN: 4026397638899











List price: 451.01 €

incl. 19% VAT.

Features:

- 30 cm (12") bass speaker with 63 mm voice coil
- Class D amplifier with 300 W
- XLR inputs and parallel outputs L/R
- XLR output L/R with high-pass filter
- Adjustable crossover frequency 80-200 Hz
- Black metal grille with acoustic foam
- Rugged carrying handle
- For application areas such as: Clubs/dancing school; installation; mobile use; mobile djs / entertainer; rental

Package contents

- 1 x user manual, 1 x bass, 1 x power cord

Technical specifications:

230 V AC, 50 Hz
650 W
Protection class I
Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
5 x 20 mm, T 3,15 A fuse replaceable
Rated: 300W RMS

Logistic

EAN / GTIN: 4026397638899 Weight: 24,20 kg Length: 0.51 m Width: 0.57 m Heigth: 0.47 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Frequency range:	40 - 250 Hz
Sensitivity:	93 dB (1W/1m)
Attachment system:	M20 thread
Circuitry:	Class D
Control elements:	Phase reversal switch
Controls:	Limiter
Status LED:	Limit, power, signal
Connections:	Input: line via 2 x 3-pin XLR Output: line via 2 x 3-pin XLR Output: high-pass via 2 x 3-pin XLR
Crossover frequency:	80-200 Hz
Speaker:	1 x woofer 12" Voice coil lows 2,5"
Type of speaker:	Subwoofer
Type of construction:	Vented
Carrying handle:	1 pc/pcs
Material:	MDF (medium density fiberboard), 15 mm
Color:	Black, textured coating, painted
Dimensions:	Width: 50 cm Depth: 57,5 cm Height: 45 cm
Weight:	22,70 kg