

OMNITRONIC AZX-118A PA Subwoofer active 400W

Active 18" PA bassreflex subwoofer, 400 W RMS

Art. No.: 11039046

GTIN: 4026397638936











List price: 653.31 €

incl. 19% VAT.

Features:

- 46 cm (18") bass speaker with 76 mm voice coil
- Class D amplifier with 400 W
- XLR inputs and parallel outputs L/R
- XLR output L/R with high-pass filter
- Adjustable crossover frequency 80-200 Hz
- Black metal grille with acoustic foam
- Rugged carrying handle
- For application areas such as: Clubs/dancing school; installation; mobile use; mobile djs / entertainer; rental

Package contents

- 1 x bass, 1 x user manual, 1 x power cord

Technical specifications:

230 V AC, 50 Hz
650 W
Protection class I
Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
5 x 20 mm, T 3,15 A fuse replaceable
Rated: 400W RMS

Logistic

EAN / GTIN: 4026397638936 Weight: 34,90 kg Length: 0.68 m Width: 0.67 m Heigth: 0.60 m Bulky product

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Frequency range:	40 - 250 Hz
Sensitivity:	95 dB (1W/1m)
Attachment system:	Flange: M20 thread
Circuitry:	Class D
Control elements:	Phase reversal switch
Controls:	Limiter
Status LED:	Limit, power, signal
Connections:	Input: line via 2 x 3-pin XLR
	Output: line via 2 x 3-pin XLR
	Output: high-pass via 2 x 3-pin XLR
Crossover frequency:	80-200 Hz
Speaker:	1 x woofer 18"
	Basket material: steel
	Voice coil lows 2,5"
Type of speaker:	Subwoofer
Type of construction:	Vented
Carrying handle:	1 pc/pcs
Material:	MDF (medium density fiberboard), 15 mm
Color:	Black, textured coating, painted
Dimensions:	Width: 61,3 cm
	Depth: 61,3 cm
	Height: 54 cm
Weight:	32,70 kg