OMNITRONIC MOLLY-12A Subwoofer active white

Active 12" subwoofer with DSP and Bluetooth

Art. No.: 11039051

GTIN: 4026397680126

List price: 677.11 €

incl. 19% VAT.

Features:

- 12" bassreflex subwoofer with DSP and 700 watts RMS power
- Flexibly extendable with MOLLY-6 satellites for 2.1 and 4.1 configurations
- DSP-controlled class D amplifier (500 W + 2 x 100 W)
- Separate volume control for subwoofer and satellites
- Stereo/mono selection
- Digital signal processor
- Control via Bluetooth
- For application areas such as: Mobile djs / entertainer; Trade fair and shop fitting; Installation; home entertainment; restaurants, bars and hotels; product presentations and lectures
- White metal grille with acoustic foam
- 2 Rugged carrying handles
- DSP presets: FLAT; DJ; LIVE; VOICE

Package contents

- 1 x bass, 1 x power cord, 2 x speaker cable, 1 x user manual, 1 x declaration of conformity

Logistic

EAN / GTIN: 4026397680126

Weight: 23,85 kg

Length: 0.62 m

Width: 0.52 m

Heigth: 0.47 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	1000 W
Output power:	1 x 500 W RMS; 2 x 100 W RMS (8 ohms); 2 x 200 W RMS (4 ohms)

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Frequency range:	40 - 160 Hz
Sensitivity:	103 dB
Max. SPL:	128 dB
DSP:	Digital signal processor
DSP presets:	FLAT; DJ; LIVE; VOICE
Control:	Bluetooth
Attachment system:	Flange: M20 thread
Circuitry:	Class D
Control elements:	Phase reversal switch
Controls:	Limiter
Status LED:	Signal, power, limit, fault, DSP presets
Connections:	Input: line via 2 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Input: line via 1 x 3.5 mm jack (stereo) mounting version Input: line via 1 x stereo RCA Output: line via 2 x 3-pin XLR Output: Top via 2 x speaker built-in socket (F)
Input channels:	1 x stereo via Combination socket or RCA or Bluetooth, channel control via Rotary dial
Speaker:	1 x woofer 12" Voice coil lows 3"
Type of speaker:	Subwoofer
Type of construction:	Vented
Carrying handle:	2 pc/pcs
Material:	Birch multiplex
Color:	White, textured coating, painted
Dimensions:	Width: 47 cm Depth: 57 cm Height: 40 cm
Weight:	22,10 kg
Speaker cable	
Cable length:	3 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.