

## OMNITRONIC MAXX-1206DSP 2.1 Active Subwoofer 12"

High-power 12" active subwoofer with DSP and Bluetooth, 450 watts

Art. No.: 11039062

GTIN: 4026397722215



**List price: 510.51 €**

incl. 19% VAT.

### Features:

- 12" subwoofer with Class D amplifier in bassreflex cabinet
- Amplifier power: 250 W RMS + 2 x 100 W RMS for two satellites
- Serves as a mobile 2.1 system together with MAXX-1206 2-way tops
- Balanced signal input XLR/6.3 mm jack L/R
- Additional stereo RCA input, with level switch
- Separate volume control for subwoofer and satellites
- Stereo/mono selection
- Digital signal processor
- DSP presets: FLAT; DJ; LIVE
- Control via Bluetooth
- Black metal grille with acoustic foam
- Rubber feet
- Wheels optional
- For application areas such as: Mobile djs / entertainer; Trade fair and shop fitting; installation; home entertainment; restaurants, bars and hotels; product presentations and lectures
- Application possibility: Standing

#### Package contents

- 1 x bass, 1 x power cord, 1 x user manual, 1 x declaration of conformity

### Logistic

EAN / GTIN: 4026397722215

Weight: 20,60 kg

Length: 0.53 m

Width: 0.43 m

Height: 0.53 m

### Technical specifications:

Power supply: 230 V AC, 50 Hz

Power consumption: 500 W

Protection class: Protection class I

Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug included
Device fuse:	5 x 20 mm, T 4 A fuse replaceable
Power:	Rated: 250W RMS LF Rated: 2x 100W RMS HF
Frequency range:	100 - 17000 Hz top
Sensitivity:	97 dB
Max. SPL:	119 dB
DSP:	Digital signal processor
DSP presets:	FLAT; DJ; LIVE
Control:	Bluetooth
Bluetooth device name:	OMNITRONIC MAXX1206
Attachment system:	Flange: M20 thread
Circuitry:	Class D
Control elements:	Power switch, level control, Input sensitivity switch, connect, tone control
Controls:	Limiter
Status LED:	Power, signal, limit, pairing, DSP presets
Connections:	Input: line via 1 x stereo RCA Input: line via 2 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Output: line via 2 x 3-pin XLR Output: speaker via 2 x speaker built-in socket (F)
Input channels:	1 x stereo via XLR or RCA or bluetooth, channel control via rotary dial
Speaker:	1 x woofer 12" with ferrit magnet Basket material: steel Conematerial: cardboard/paper
USB port:	1 x type C, 2 A
Type of speaker:	Subwoofer
Type of construction:	Vented
Transport aid:	Rubber feet Wheels optional
Material:	MDF (medium density fiberboard), 16 mm
Color:	Black, textured coating, painted
Dimensions:	Width: 38,4 cm Depth: 47,4 cm Height: 45,8 cm
Weight:	19,10 kg
Bass	
Frequency range:	38 - 250 Hz bass