

## OMNITRONIC MAXX-1206DSP 2.1 Active Subwoofer 12" white

High-power 12" active subwoofer with DSP and Bluetooth, 450 watts

Art. No.: 11039065

GTIN: 4026397722246



**List price: 534.31 €**

incl. 19% VAT.

### Features:

- 12" subwoofer with Class D amplifier in bassreflex cabinet
- Amplifier power: 250 W RMS + 2 x 100 W RMS for two satellites
- Serves as a mobile 2.1 system together with MAXX-1206 2-way tops
- Balanced signal input XLR/6.3 mm jack L/R
- Additional stereo RCA input, with level switch
- Separate volume control for subwoofer and satellites
- Stereo/mono selection
- Digital signal processor
- DSP presets: FLAT; DJ; LIVE
- Control via Bluetooth
- White metal grille with acoustic foam
- Rubber feet
- Wheels optional
- Application possibility: Standing

#### Package contents

- 1 x bass, 1 x power cord, 1 x strap, 1 x user manual, 1 x declaration of conformity

### Logistic

EAN / GTIN: 4026397722246

Weight: 21,00 kg

Length: 0.53 m

Width: 0.44 m

Height: 0.52 m

### Technical specifications:

Power supply: 230 V AC, 50 Hz

Power consumption: 500 W

Protection class: Protection class I

|                        |                                                                                                                                                                                                                                     |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power connection:      | Mains input via IEC connector (M) mounting version power supply cord with safety plug included                                                                                                                                      |
| Device fuse:           | 5 x 20 mm, T 4 A fuse replaceable                                                                                                                                                                                                   |
| Power:                 | Rated: 250W RMS LF<br>Rated: 2x 100W RMS HF                                                                                                                                                                                         |
| Frequency range:       | 38 - 250 Hz bass<br>100 - 17000 Hz top                                                                                                                                                                                              |
| Sensitivity:           | 97 dB                                                                                                                                                                                                                               |
| Max. SPL:              | 119 dB                                                                                                                                                                                                                              |
| DSP:                   | Digital signal processor                                                                                                                                                                                                            |
| DSP presets:           | FLAT; DJ; LIVE                                                                                                                                                                                                                      |
| Control:               | Bluetooth                                                                                                                                                                                                                           |
| Bluetooth device name: | OMNITRONIC MAXX1206                                                                                                                                                                                                                 |
| Attachment system:     | Flange: M20 thread                                                                                                                                                                                                                  |
| Circuitry:             | Class D                                                                                                                                                                                                                             |
| Control elements:      | Power switch, level control, Input sensitivity switch, connect, tone control                                                                                                                                                        |
| Controls:              | Limiter                                                                                                                                                                                                                             |
| Status LED:            | Power, signal, limit, pairing, DSP presets                                                                                                                                                                                          |
| Connections:           | Input: line via 1 x stereo RCA<br>Input: line via 2 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version)<br>Output: line via 2 x 3-pin XLR (M) mounting version<br>Output: speaker via 2 x speaker built-in socket (F) |
| Input channels:        | 1 x stereo via XLR or RCA or bluetooth, channel control via rotary dial                                                                                                                                                             |
| Speaker:               | 1 x woofer 12" with ferrit magnet<br>Basket material: steel<br>Conematerial: cardboard/paper                                                                                                                                        |
| USB port:              | 1 x type C, 2 A                                                                                                                                                                                                                     |
| Type of speaker:       | Subwoofer                                                                                                                                                                                                                           |
| Type of construction:  | Vented                                                                                                                                                                                                                              |
| Transport aid:         | Rubber feet<br>Wheels optional                                                                                                                                                                                                      |
| Material:              | MDF (medium density fiberboard), 16 mm                                                                                                                                                                                              |
| Color:                 | White, textured coating, painted                                                                                                                                                                                                    |
| Dimensions:            | Width: 38,4 cm<br>Depth: 47,4 cm<br>Height: 45,8 cm                                                                                                                                                                                 |
| Weight:                | 19,50 kg                                                                                                                                                                                                                            |