

OMNITRONIC PAS-212PRO 2-way Top

2-way speaker system for PA applications

Art. No.: 11039444

GTIN: 4026397438390



Features:

- PA speaker system for medium-sized and large discotheques
- Rugged full-range top speaker qualified for suspended installation
- Rotatable constant directivity horn (asymmetrical) with coil-driver
- Passive 2-way crossover, PTC tweeter protection
- Bass-reflex system for powerful, dry bass
- Balanced frequency range with high sound-pressure
- Very high durability
- Optimized for combination with PAS subwoofers
- Scratch-resistant lacquer surface
- Impact-resistant steel grille with acoustic foam
- Flange for stand installation
- Trapezoidal wooden housing with monitor shape
- Can be used lying, standing, on a subwoofer, on a speaker stand or stand or suspended
- Suitable for car transport
- The combination of several PAS speakers allows for large PA systems

Logistic

EAN / GTIN: 4026397438390

Weight: 18,55 kg

Length: 0.44 m

Width: 0.41 m

Height: 0.68 m

Technical specifications:

Frequency range: 60 - 20000 Hz

Dimensions: Width: 35.5 cm

Depth: 33 cm

Height: 60 cm

Weight: 16.80 kg

Rated power:	300 W RMS
Program power:	600 W
Components:	30 cm woofer (12"), 2.5 cm horn (1")
Connection:	2 Speaker sockets
Sensitivity:	97 dB
Maximum SPL:	122 dB
Impedance:	8 ohms
Crossover frequency:	2 kHz
Dispersion angle:	50-100° x 55°

Scope of delivery: