

OMNITRONIC PAS-151A MK3 Subwoofer, active, DSP

Active 15" PA bassreflex subwoofer, 700 W RMS

Art. No.: 11039487

GTIN: 4026397672619



The article is no longer in our assortment.

Features:

- Active PA subwoofer for touring applications and permanent installations
- 38 cm (15") bass speaker with 100 mm voice coil
- DSP-controlled class D amplifier with 700 watts power
- XLR outputs with switchable high-pass filter, 120 Hz
- Digital signal processor
- DSP presets: FLAT; DJ; LIVE
- Black metal grille with acoustic foam
- 2 Rugged carrying handles
- Wheels optional

Package contents

- 1 x user manual, 1 x power cord, 1 x bass

Logistic

EAN / GTIN: 4026397672619

Weight: 36,00 kg

Length: 0.62 m

Width: 0.52 m

Height: 0.58 m

Bulky product

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	800 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power:	Rated: 700W RMS
Frequency range:	40 - 200 Hz
Max. SPL:	125 dB

DSP:	Digital signal processor
DSP presets:	FLAT; DJ; LIVE
Attachment system:	Flange: M20 thread
Circuitry:	Class D
Control elements:	Phase reversal switch
Controls:	Limiter; power on/off transient
Status LED:	Limit, power, signal, DSP presets
Connections:	Input: line via 2 x 3-pin XLR (F) mounting version Output: line via 2 x 3-pin XLR (M) mounting version
Input channels:	Stereo via XLR, channel control via rotary dial
Speaker:	1 x woofer 15" with ferrit magnet Basket material: aluminum Voice coil lows 4"
Type of speaker:	Subwoofer
Type of construction:	Vented
Carrying handle:	2 pc/pcs
Transport aid:	Wheels optional
Material:	Birch multiplex
Color:	Black, textured coating, painted
Dimensions:	Width: 46 cm Depth: 56 cm Height: 52 cm
Weight:	33,50 kg