

OMNITRONIC PAS-181A PRO DSP Active Subwoofer

Active 18" PA bassreflex subwoofer, 1200 W

Art. No.: 11039631

GTIN: 4026397527469



The article is no longer in our assortment.

Features:

- Active high-power bassreflex subwoofer for permanent installations and touring purposes
- Housing made of 18 mm plywood multilayered glued
- 1200 W Class D power amplifier with switch mode power supply
- 45 cm (18") bass speaker
- Balanced XLR input L/R
- Parallel XLR line output L/R
- Adjustable crossover frequency 80-200 Hz
- DSP-controlled limiter
- Phase reversal switch
- M20 metal flange for mounting top speakers
- Incorporated carrying handles
- Scratch-resistant lacquer surface, steel grille and rubber feet
- Matching castors optionally available
- Digital signal processor
- Wheels optional

Logistic

EAN / GTIN: 4026397527469

Weight: 61,40 kg

Length: 0.91 m

Width: 0.66 m

Height: 0.80 m

Bulky product

Technical specifications:

| | |
|--------------------|--|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | 670 W |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |

| | |
|-----------------------|---|
| Power: | Program: 1200W Rated: 600W RMS |
| Frequency range: | 40 - 120 Hz |
| Sensitivity: | 96 dB |
| Max. SPL: | 126 dB |
| DSP: | Digital signal processor |
| Attachment system: | Ø 35mm |
| Circuitry: | Class D |
| Connections: | Input: line via 2 x 3-pin XLR Output: line via 2 x 3-pin XLR |
| Crossover frequency: | 80-200 Hz |
| Speaker: | 1 x woofer 18" |
| Type of speaker: | Subwoofer |
| Type of construction: | Vented |
| Transport aid: | Wheels optional |
| Dimensions: | Width: 56 cm Depth: 80 cm Height: 69 cm |
| Weight: | 54,70 kg |