

PSSO CSA-228W top, white

Compact speaker array for touring purposes and permanent installations

Art. No.: 11040801 GTIN: 4026397362831





The article is no longer in our assortment.

Description:

The CSA high-mid speaker units,

they are very powerful and feature a horn tweeter with 3.5 cm driver and, depending on the model, one or two 20 cm woofers (CSA-218 or CSA-228 respectively). The tweeter of the smaller version, the CSA-218, ensures a horizontal and vertical dispersion angle of 90° . Thus the CSA-218 can be used standing or lying without having to make compromises in terms of sound or directivity. The larger version, the CSA-228, is designed for upright use and has a dispersion angle of 90° x 40° .

Where should the CSA be used?

We can recommend mobile use. Concerts or weddings are supported in a powerful, resonant and linear way. But as it is quite versatile, the CSA should not be reduced to our suggestion only.

Features:

- Compact speaker array for permanent installations and touring purposes
- Horn tweeter for powerful highs
- Lightweight housing due to high-quality plastic
- Wide horizontal dispersion angle

Technical specifications:

Frequency range: 75 - 18000 Hz

Dimensions: Width: 66,5 cm

Logistic

EAN / GTIN: 4026397362831

Weight: 16,75 kg Length: 0.75 m Width: 0.42 m Heigth: 0.38 m

| Depth: 34 cm |
|---------------|
| Height: 25 cn |
| 14 E0 kg |

| | 3 |
|-------------------------|---|
| Weight: | 14,50 kg |
| Rated power: | 300 W RMS |
| Program power: | 600 W |
| Components: | 2×20 cm woofer (2 x 8"), 3.4 cm driver (1.33") |
| Connection: | 2 Speaker sockets (4-pin) |
| Sensitivity: | 95 dB |
| Maximum SPL: | 119 dB |
| Impedance: | 8 ohms |
| Crossover frequency: | 2.5 kHz |
| Dispersion angle: | H=90°, V=40° |
| Dimensions (H x W x D): | 250 x 665 x 340 mm |