

**PSSO CSA-115CXA Active Subwoofer black**

Active 15" PA bassreflex subwoofer, 1000 W

**Art. No.: 11040819**

GTIN: 4026397527667

**The article is no longer in our assortment.****Features:**

- Active high-power bassreflex subwoofer for permanent installations and touring purposes
- High-performance Class D power amplifier (1000 W) with switch mode power supply
- 38 cm (15") bass speaker
- Balanced XLR input
- XLR line output with high-pass filter (100 Hz) for the active top speakers CSA-218A and CSA-228A
- PowerCon mains input with parallel output for power supply of one top speaker (CSA-218A/CSA-228A)
- Limiter and protection set against short-circuit, overheat and overload
- MDF housing (18 mm) with scratch-resistant lacquer surface, steel grille and flange
- Carrying handles and rubber feet
- Stackable

**Logistic**

EAN / GTIN: 4026397527667

Weight: 43,35 kg

Length: 0.73 m

Width: 0.53 m

Height: 0.75 m

Bulky product

**Technical specifications:**

|                      |                         |
|----------------------|-------------------------|
| Power supply:        | 230 V AC, 50 Hz         |
| Power:               | 1000W                   |
| Frequency range:     | 35 - 95 Hz              |
| Speaker:             | 15"                     |
| Rated power:         | 1000 W                  |
| Components:          | LF: 38 cm (15")         |
| Crossover frequency: | HPF: 30 Hz, LPF: 100 Hz |

|                      |  |
|----------------------|--|
| Dispersion angle:    | -  |
| Maximum SPL:         | 123 dB                                     |
| Acoustic loading:    | Bassreflex                                 |
| Cabinet material:    | MDF (18 mm)                                |
| Amplifier:           | Class D                                    |
| THD:                 | <0.1 %                                     |
| S/N ratio:           | >80 dB                                     |
| Damping factor:      | >50  |
| Input sensitivity:   | 2 V  |
| Input impedance:     | 40 kohms/20 kohms (bal./unbal.)            |
| Signal input:        | XLR  |
| Signal output:       | XLR (HPF 100 Hz)                           |
| Power consumption:   | 1000 W                                     |
| Protection circuits: | Limiter, overheat, overload, short-circuit |
| LED indicators:      | Power, signal, clip                        |
| Weight:              | 37 kg                                      |