

PSSO K-315HD 3-Way Top 1000W

PRO PA speaker, 15" woofer, 6.5" mid, 1.4" horn, 1000 W RMS (Biamp)

Art. No.: 11041112

GTIN: 4026397483079



Features:

- Rugged full-range top speaker, qualified for suspension and touring applications
- Biamp operation
- Housing made of 15 mm/18 mm birch plywood
- 38 cm neodymium bass speaker (15") and 16.5 cm midrange speaker (6.5") with diecast aluminum basket
- 36 mm neodymium hybrid horn tweeter (1.4") with 72 mm voice coil (2.8")
- Premium custom-made drivers by European manufacturer CELTO Acoustique
- Bassreflex system
- Parallel Neutrik Speakon connectors
- Trapezoidal multi-functional housing with scratch-resistant lacquer surface
- Impact-resistant steel grille with acoustic foam
- Flange for stand installation
- Applications: standing, on a subwoofer or speaker stand, suspended
- CELTO ACOUSTIQUE driver
- European engineering

Logistic

EAN / GTIN: 4026397483079

Weight: 40,70 kg

Length: 0.56 m

Width: 0.55 m

Height: 0.92 m

Bulky product

Technical specifications:

| | |
|------------------|-----------------------------------|
| Power: | Program: 1400W Rated: 700W RMS |
| Frequency range: | 45 - 20000 Hz |
| Sensitivity: | 108 dB MHF; 98 dB LF |
| Max. SPL: | 137 dB |

| | |
|----------------------|-----------------------------------------------------------------------|
| Impedance: | 4/8 ohms biamp |
| Connections: | Input: speaker via 2 x speaker built-in socket (F) |
| Crossover frequency: | 2500 Hz 500 Hz |
| Speaker: | 1 x woofer 15" |
| Type of speaker: | Compact cabinet speaker |
| Use of brands: | CELTO ACOUSTIQUE driver |
| Dimensions: | Width: 45 cm Depth: 44.3 cm Height: 80 cm |
| Weight: | 36.75 kg |
| | 300 W RMS MHF |
| Components: | 38 cm woofer (15"), 16.5 cm driver (6.5"), 3.6 cm horn tweeter (1.4") |
| Connection: | 2 x Speakon |
| Impedance: | |
| LF: | 8 ohms |
| MHF: | 8 ohms |
| Dispersion angle: | 70° x 40° above 600 Hz |

Scope of delivery:
