

## PSSO KX-181A Subwoofer, active, DSP

Active 18" PA bassreflex subwoofer, 1400 W RMS

Art. No.: 11041182

GTIN: 4026397745375



**List price: 1069.81 €**

incl. 19% VAT.

### Features:

- Active PA subwoofer for touring applications and permanent installations
- Versatile setup options with the KX top speakers and specially tuned presets
- Endfire and cardioid array configurations possible
- Digital signal processor
- DSP presets: 80 Hz hi cut; 90 Hz hi cut; 100 Hz hi cut; 120 Hz hi cut; End Fire 80 Hz; Inverted/Cardioid 80 Hz
- The device is cooled by temperature-controlled fan
- Black metal grille with acoustic foam
- 4 Rugged carrying handles
- Mains input and output for power linking up to 4 units

#### Package contents

- 1 x bass, 1 x power cord, 1 x user manual

### Logistic

EAN / GTIN: 4026397745375

Weight: 57,65 kg

Length: 0.83 m

Width: 0.64 m

Height: 0.70 m

Bulky product

### Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	1800 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version

Device fuse:	5 x 20 mm, F 8 A fuse replaceable
Power:	1400W RMS Peak: 2800W
Frequency range:	30 - 400 Hz
Max. SPL:	134 dB
DSP:	Digital signal processor
DSP presets:	80 Hz hi cut; 90 Hz hi cut; 100 Hz hi cut; 120 Hz hi cut; End Fire 80 Hz; Inverted/Cardioid 80 Hz
Cooling:	1 x temperature-controlled fan
Attachment system:	M20 thread
Circuitry:	Class D
Control elements:	Power switch, groundlift selector, level control, DSP preset switch
Controls:	Overheat; short-circuit; DC voltage; limiter
Status LED:	Power, signal, clip
Connections:	Input: line via 2 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Output: line via 2 x 3-pin XLR (M) mounting version
Speaker:	1 x woofer 18" with ferrit magnet Basket material: aluminum Conematerial: cardboard/paper Voice coil woofer in/out wound 4"
Type of speaker:	Subwoofer
Type of construction:	Vented
Carrying handle:	4 pc/pcs
Material:	Baltic birch plywood, 18 mm
Color:	Black, matte
Dimensions:	Width: 56 cm Depth: 76 cm Height: 62,8 cm
Weight:	53,25 kg
Power cord	
Cable construction:	3 x 0,75 mm² H05VV-F
Cable length:	2,5 m detachable