

CELTO ACOUSTIQUE CMP10 2-way Coaxial Speaker

Art. No.: 11043630

GTIN:



List price: on demand €

incl. 19% VAT.

Features: Logistic

- With rigging points
- CELTO ACOUSTIQUE driver
- Built with NEUTRIK connector
- Rubberized Polyurea coating
- For application areas such as: Concerts/FoH's; clubs/dancing school; wedding/gala/events;
 Trade fair and shop fitting; installation; mobile use; stage; theater; rental; product presentations and lectures; trade fair construction

Package contents

- 1 x top

Technical specifications:

Power:	Peak: 1200W	
	Program: 600W	
	Rated: 300W AES	
Frequency range:	78 - 22000 Hz	
Sensitivity:	97 dB (1W/1m)	
Max. SPL:	128 dB	
Dispersion angle:	80° conical	
Impedance:	8 ohms	
Flying points:	7 x M8 thread	

Control elements:	Mode switch (1+1- / 2+2-)
Connections:	2 x 4-pol SpeakON mounting version (F)
Crossover frequency:	1500 Hz
Speaker:	1 x woofer 10" with ferrit magnet
	Basket material: aluminum
	Voice coil lows 2,5"
	1 x annular compression driver 1" with neodymium magnet
	Voice coil annular 1,75"
	Diaphragmmaterial: PEEK (H.T. polymer)
Type of speaker:	Coaxial speaker; compact cabinet speaker
Type of construction:	Vented
Use of brands:	CELTO ACOUSTIQUE driver
	Built with NEUTRIK connector
Material:	Birch multiplex
Color:	Black, rubberized Polyurea coating
Dimensions:	Width: 44 cm
	Depth: 29,8 cm
	Height: 30,6 cm
Weight:	15,00 kg