

## **CELTO ACOUSTIQUE CT15 G2 2-Way Fullrange Loudspeaker**

Art. No.: 11043669

GTIN:



## The article is no longer in our assortment.

Features: Logistic

- Horn 90 degree rotatable for horizontal or vertical use
- With rigging points

Package contents

1 x top

## **Technical specifications:**

| Power:               | Program: 1400W                         |
|----------------------|----------------------------------------|
|                      | Rated: 700W RMS                        |
| Frequency range:     | 48 - 22000 Hz                          |
| Sensitivity:         | 98 dB (1W/1m)                          |
| Max. SPL:            | 133 dB                                 |
| Dispersion angle:    | 80° x 50° rotatable horn               |
| Impedance:           | 8 ohms                                 |
| Flying points:       | 16 x M8 thread                         |
| Connections:         | 2 x 4-pol SpeakON mounting version (F) |
| Crossover frequency: | 1400 Hz                                |
| Speaker:             | 1 x woofer 15"                         |
|                      | Basket material: aluminum              |
|                      | Voice coil lows 3,5"                   |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted. Illustration only. Actual item may differ from photo.

Diaphragmmaterial: PEEK (H.T. polymer) 1 x Annular compression driver 1"

Voice coil annular 1,75"

| Type of speaker: | Compact cabinet speaker |
|------------------|-------------------------|
| Material:        | Birch multiplex         |
| Color:           | Black, matte            |
| Dimensions:      | Width: 71 cm            |
|                  | Depth: 41,4 cm          |
|                  | Height: 44,5 cm         |
| Weight:          | 28,35 kg                |