

CELTO ACOUSTIQUE VCM10 2-Way Coaxial Monitor

Compact and low-profile coaxial monitor

Art. No.: 11043670

GTIN:



List price: on demand €

incl. 19% VAT.

Features:

- Real 300 W AES with high-end sound quality
- Natural sound and incredible holographic reproduction
- Optimized for smooth frequency response in and out axis
- Premium Neodymium custom made driver
- Dual monitor angle, for short monitoring
- With rigging points
- High-quality workmanship with birch multiplex , black, rubberized Polyurea coating
- For application areas such as: Concerts/FoH's; Clubs/dancing school; theater; restaurants, bars and hotels; Installation

Logistic

Technical specifications:

Power:	Program: 600W Rated: 300W RMS
Frequency range:	75 - 18000 Hz
Sensitivity:	98 dB
Max. SPL:	131 dB
Dispersion angle:	80° conical
Impedance:	8 ohms
Flying points:	14 x M8 thread
Crossover frequency:	Passive 1600 Hz, 12db/oct on LF

Passive 1600 Hz, 24db/oct on HF
Recommended
Low-pass 150 Hz, 24db/oct in full-range mode
Low-pass 60-120 Hz with subwoofer

Material:	Birch multiplex
Color:	Black, rubberized Polyurea coating
Dimensions:	Width: 44,8 cm Depth: 37,6 cm Height: 27,7 cm
Weight:	13,80 kg
