

CELTO ACOUSTIQUE SU218TL Transmission Line Subwoofer

Large-scale subwoofer, maximum SPL

Art. No.: 11043690 GTIN: 4026397664041











List price: on demand €

incl. 19% VAT.

Features:

- Rear-loaded transmission line subwoofer
- Down to 28Hz at -6dB and still 104dB/1W/1m efficiency
- Real 3000 W RMS power capacity
- Premium 18" LF drivers with massive ±15 mm linear Xmax
- Triple-forced cooling system for low power compression
- Heavy braced cabinet for vibration free dynamic response
- CELTO ACOUSTIQUE driver
- Built with NEUTRIK connector
- Rubberized Polyurea coating
- For application areas such as: Theater; sports centres/gyms; clubs/dancing school

Package contents

- 1 x bass

Logistic

EAN / GTIN: 4026397664041

Weight: 124,65 kg Length: 0.85 m Width: 0.70 m Heigth: 1.40 m Bulky product

Technical specifications:

| Power: | Peak: 12000W |
|-------------------|------------------|
| | Program: 6000W |
| | Rated: 3000W AES |
| Frequency range: | 26 - 900 Hz |
| Sensitivity: | 104 dB (1W/1m) |
| Max. SPL: | 145 dB |
| Dispersion angle: | Omnidirectional |

| Impedance: | 4 ohms |
|-----------------------|--|
| Attachment system: | Flange: 2x M20 thread |
| Connections: | Input: speaker via 3 x 4-pol SpeakON mounting version (F) |
| Crossover frequency: | Recommended |
| | High-pass 28 Hz, 24db/oct |
| | Low-pass 80-110 Hz |
| Speaker: | 2 x woofer 18" with ferrit magnet |
| | Basket material: aluminum |
| | Voice coil woofer in/out wound 4" |
| Type of speaker: | Subwoofer |
| Type of construction: | Transmission line |
| Use of brands: | CELTO ACOUSTIQUE driver |
| | Built with NEUTRIK connector |
| Material: | Baltic birch plywood, 18 mm, CNC made with tongue and grove assembly |
| Color: | Black, rubberized Polyurea coating, painted |
| Dimensions: | Width: 124,6 cm |
| | Depth: 72,8 cm |
| | Height: 58,0 cm |
| Weight: | 111,00 kg |