

## CELTO ACOUSTIQUE SU218TL Transmission Line Subwoofer

Large-scale subwoofer, maximum SPL

Art. No.: 11043690

GTIN: 4026397664041



**List price: on demand €**

incl. 19% VAT.

### Features:

- Rear-loaded transmission line subwoofer
- Down to 28Hz at -6dB and still 104dB/1W/1m efficiency
- Real 3000 W RMS power capacity
- Premium 18" LF drivers with massive  $\pm 15$  mm linear Xmax
- Triple-forced cooling system for low power compression
- Heavy braced cabinet for vibration free dynamic response
- For application areas such as: Theater; sports centres/gyms; Clubs/dancing school
- CELTO ACOUSTIQUE driver
- Built with NEUTRIK connector
- Rubberized Polyurea coating

#### Package contents

- 1 x bass

### Logistic

EAN / GTIN: 4026397664041

Weight: 124,65 kg

Length: 0.85 m

Width: 0.70 m

Height: 1.40 m

Bulky product

### Technical specifications:

|                   |  |
|-------------------|--|
| Power:            | Rated: 3000W AES<br>Program: 6000W<br>Peak: 12000W |
| Frequency range:  | 26 - 900 Hz  |
| Sensitivity:      | 104 dB (1W/1m)                                     |
| Max. SPL:         | 145 dB   |
| Dispersion angle: | Omnidirectional                                    |

|                       |  |
|-----------------------|--|
| Impedance:            | 4 ohms   |
| Attachment system:    | Flange: 2x M20 thread  |
| Connections:          | Input: speaker via 3 x speaker built-in socket (F)                                   |
| Crossover frequency:  | Recommended<br>High-pass 28 Hz, 24db/oct<br>Low-pass 80-110 Hz                       |
| Speaker:              | 2 x woofer 18" with ferrit magnet<br>Basket material: aluminum<br>Voice coil lows 4" |
| Type of speaker:      | Subwoofer  |
| Type of construction: | Transmission line  |
| Use of brands:        | CELTO ACOUSTIQUE driver<br>Built with NEUTRIK connector                              |
| Material:             | Baltic birch plywood, 18 mm, CNC made with<br>tongue and grove assembly              |
| Color:                | Black, rubberized Polyurea coating, painted  |
| Dimensions:           | Width: 1,246 m<br>Depth: 72,8 cm<br>Height: 58,0 cm                                  |
| Weight:               | 111,00 kg  |