

CELTO T4.26 Amplifier

Class D touring amplifier with SMPS, 4 x 2600 W RMS (4 ohms), 4 x 1400 W RMS (8 ohms)

Art. No.: 11043806

GTIN: 4026397662733



Features:

- (19") 48.3 cm rack installation 2 U
- Highly efficient air flow from front to rear
- The device is cooled by cooling fan

Logistic

EAN / GTIN: 4026397662733

Weight: 16,25 kg

Length: 0.54 m

Width: 0.58 m

Height: 0.17 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Protection class:	Protection class I
Output power:	4 x 2600 W RMS (4 ohms) 4 x 1400 W RMS (8 ohms)
Power connection:	Mains input via P-Con (blue), mounting version (provided)
Cable length:	1.5 m detachable
Cooling:	3 x cooling fan , air flow from front to rear
Gain:	34 dB/ 2.82 V
Circuitry:	Class D
Slew rate:	>60 V/ μ s
Damping factor:	>800
Status LED:	Power, signal, limit, protect, SOM

Connections:	Input: line via 4 x 3-pin XLR Output: line via 4 x 3-pin XLR Output: speaker via 4 x 4-pol SpeakON mounting version (F)
Housing design:	(19") 48.3 cm rack installation 2 U
Dimensions:	Width: 48.3 cm Depth: 46.8 cm Height: 8.8 cm
Weight:	15.85 kg

Scope of delivery:

1 x amplifier
1 x power cord
4 x foot