

## INTUSONIC 6FP100T 6.5" 2-Way Full-range Speaker black

6.5" installation speaker 80W AES, 8 ohms, 116.5 dB max. SPL

Art. No.: 12604003

GTIN: 5060502923035



**List price: on demand €**

incl. 19% VAT.

### Description:

The INTUCAB 6FP100T is the most universal choice for audio systems requiring a small footprint, without sacrifice to sound quality and SPL. The multitude of connections (Speakon-compatible and 5mm terminal strip), as well as the available input transformer option for 100V systems, contribute further to its versatility. Mounting options include VESA, M6 and M10 mounting points, plus the (patent-pending) L-shaped reversible rear panel allowing for suspended mounting, truss mounting and bracket mounting. Available in black and white structural paint finish. Add the INTUCAB 8SM300T Subwoofer for extended low frequency performance.

### Logistic

EAN / GTIN: 5060502923035

Weight: 8,85 kg

Length: 0.37 m

Width: 0.32 m

Height: 0.30 m

### Features:

- Reversible rear panel with 3 mounting options
- 1" HF compression driver & wide-dispersion HF horn
- Advanced passive crossover for best sound quality
- 100V transformer kit option (UTK20 - sold separately)
- Horn 90 degree rotatable for horizontal or vertical use
- With rigging points
- Black metal grille with acoustic foam
- For application areas such as: Installation; restaurants, bars and hotels
- For further information about this product, please refer to the Data Sheet under "Downloads"

#### Package contents

- 1 x top, 1 x user manual, 1 x screw plug-in terminal, 3 x safety eyelet

## Technical specifications:

IP classification:	IP20
Power:	Rated: 80W AES Program: 150W
Frequency range:	75 - 16500 Hz
Sensitivity:	92 dB (1W/1m)
Max. SPL:	116,5 dB
Dispersion angle:	90° x 60° rotatable horn
Impedance:	8 ohms
Attachment system:	M10 thread 3x M6 thread VESA standard
Flying points:	3 x M6 thread; 1 x M10 thread
Power tapping:	35W; 70W
Connections:	2 x speaker built-in socket (F) 1 x screw plug-in terminal
Speaker:	1 x woofer 6,5" 1 x compression tweeter highs 1"
Type of speaker:	Compact cabinet speaker
Type of construction:	Vented
Material:	MDF (Medium-density fiberboard), 12 mm
Color:	Black, textured coating, painted
VESA interface min:	7,5 cm x 7,5 cm
Dimensions:	Width: 22,5 cm Depth: 25,2 cm Height: 32,5 cm
Weight:	8,20 kg