

OMNITRONIC IC-1005 PRO Studio Microphone

PRO tube condenser microphone for studio recording

Art. No.: 13030702

GTIN: 4026397298048



The article is no longer in our assortment.

Features:

- Ideal as main and support microphone for vocals or guitars
- Far more clarity and accuracy than dynamic microphones
- Cardioid pickup pattern for effective feedback elimination
- Low-noise transformerless FET input eliminates low frequency distortion
- Balanced XLR output
- Delivery incl. power supply unit, 10 m XLR cable, shockmount, padded bag and aluminum case
- Polar pattern: Cardioid

Logistic

EAN / GTIN: 4026397298048

Weight: 4,90 kg

Length: 0.44 m

Width: 0.31 m

Height: 0.11 m

Technical specifications:

| | |
|--------------------|---------------------------------------|
| Type: | Studio microphone |
| Power consumption: | 10,00 W |
| Capsule type: | Condenser |
| Polar pattern: | Cardioid |
| Switch: | Without |
| Dimensions: | Length: 16,7 cm Diameter: Ø 6,1 cm |
| Weight: | 4,80 kg |
| Type: | Condenser |
| Polar pattern: | Cardioid |

| | |
|-------------------------|----------------------------|
| Sensitivity: | -34 dBu @ 1 kHz |
| Equivalent SPL: | 13 dBA, 20 dBC |
| Maximum SPL: | 140 dB (THD <0.5% @ 1 kHz) |
| Nominal impedance: | 250 ohms |
| Load impedance: | 200 ohms |
| Output impedance: | 1000 ohms |
| Power supply: | 48 V DC phantom power |
| Connection: | 7-pin XLR, balanced |
| | Power supply unit |
| Power supply: | 115/230 V AC, 50/60 Hz |
| Input and output: | 7-pin XLR, balanced |
| Output: | 3-pin XLR, balanced |
| Dimensions (L x W x H): | 167 x 102 x 61 mm |