Relacart®
Real Sound Always

# RELACART UH-222D Microphone 823-832 + 863-865 MHz

Hand-held microphone with PLL multifrequency transmitter

**Art. No.: 13055206**
GTIN: 4026397537031

## List price: 141.61 €

incl. 19% VAT.

## Features:

- Dynamic hand-held microphone with UHF pilot tone technology (PLL)
- Ergonomic aluminum alloy housing, applicable for touring
- 10 groups with 90 fixed frequencies within 11 MHz switching bandwidth
- Easy and error-free synchronization between receiver and transmitter via infrared signal
- RF output power Hi/Low adjustable
- Gain level Hi/Mid/Low adjustable
- Capsule M-022
- Directly compatible with Shure's SM58 capsule
- Polar pattern: Super cardoid
- Operating range up to 80m
- UHF 863 - 865 MHz License-free and approved in Europe
- UHF 823 - 832 MHz License-free and approved in large parts of Europe
- OLED display
- Charge status indicator

**Package contents**

- 1 x microphone, 1 x user manual, 1 x declaration of conformity

## Logistic

EAN / GTIN: 4026397537031
Weight: 0,42 kg
Length: 0.29 m
Width: 0.12 m
Heigth: 0.07 m

## Technical specifications:

| | |
|---|---|
| Type: | Hand-held transmitter |
| Power supply: | 3 V DC |
| Capsule type: | Dynamic |
| Polar pattern: | Super cardoid |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| | |
|---|---|
| Battery: | 2 x Mignon (AA)  (not included) |
| Frequency range: | 120 - 16000 Hz |
| Sensitivity: | -53 dB |
| Max. SPL: | 145 dB |
| Range: | Range up to 80m |
| Frequency band: | UHF 863 - 865 MHz; UHF 823 - 832 MHz |
| Switching bandwidth: | 11 MHz |
| RF power output: | 10 mW |
| Modulation: | FM |
| Frequency selection: | 90 Switchable frequencies<br>In 10 groups with up to 10 preset frequencies each |
| Display type: | OLED display |
| Display: | Charge status indicator , frequency , Chanal |
| Control elements: | Gain-switch (high-mid-low), Transmitter power switch (high-low) |
| Switch: | On/off/mute switch |
| Material: | Aluminum |
| Dimensions: | Length: 26 cm<br>Diameter: Ø 5,4 cm |
| Weight: | 280 g |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.