

## RELACART UH-200 UHF Handheld Microphone for WAM-400

Microphone with PLL multifrequency transmitter for WAM-400, 823-832 + 863-865 MHz

Art. No.: 13055219

GTIN: 4026397592436



**The article is no longer in our assortment.**

### Features:

- Dynamic hand-held microphone with UHF pilot tone technology (PLL)
- Ergonomic aluminum alloy housing, applicable for touring
- Matches receiver WAM-400
- Infrared interface for easy and error-free synchronization with the receiver via infrared signal
- Operation range approx. 80 meters
- OLED display for battery status, frequency and channel
- Mute function
- RF output power Hi/Low adjustable
- Operation via 2 x 1.5 V battery (type AA), not included
- License-free and approved in large parts of the EU (please check on a country-by-country basis)
- Polar pattern: Cardioid
- UHF 863 - 865 MHz License-free and approved in Europe
- UHF 823 - 832 MHz License-free and approved in large parts of Europe

### Logistic

EAN / GTIN: 4026397592436

Weight: 0,42 kg

Length: 0.29 m

Width: 0.12 m

Height: 0.07 m

### Technical specifications:

|                   |                                |
|-------------------|--------------------------------|
| Type:             | Hand-held transmitter          |
| Power connection: | Battery/battery pack           |
| Capsule type:     | Dynamic                        |
| Polar pattern:    | Cardioid                       |
| Battery:          | 2 x Mignon (AA) (not included) |

|                      |                                       |
|----------------------|---------------------------------------|
| Frequency band:      | UHF 863 - 865 MHz; UHF 823 - 832 MHz  |
| Frequency selection: | Switchable frequencies                |
| Switch:              | On/off switch                         |
| Material:            | Aluminum                              |
| Dimensions:          | Length: 25,5 cm<br>Diameter: Ø 5,2 cm |
| Weight:              | 290 g                                 |
| Type:                | Dynamic                               |
| Directivity pattern: | Cardioid                              |
| Switching bandwidth: | 11 MHz                                |
| RF power output:     | 10 mW (Low), 40 mW (Hi)               |
| Deviation:           | ±45 kHz                               |
| Modulation:          | FM                                    |
| Coverage:            | 60 m (with line-of-sight)             |
| Current consumption: | 110 mA                                |