

## RELACART UT-222 Bodypack with HM-600S Headset

Bodypack transmitter with PLL multifrequency transmitter, 823-832 + 863-865 MHz

Art. No.: 13055231  
GTIN: 4026397700510



**List price: 148.75 €**  
incl. 19% VAT.

### Features:

- Durable aluminum alloy housing, applicable for touring
  - Pilot frequency squelch technology delete wireless RF interference
  - 10 groups with 90 fixed frequencies within 11 MHz switching bandwidth
  - Easy and error-free synchronization between receiver and transmitter via infrared signal
  - Adjustable input gain
  - RF output power Hi/Low adjustable
  - Lock function for prevents undesired changes to settings
  - Up to 9 transmitters can be operated in parallel without interference
- transmitter**
- OLED display
  - UHF 823 - 832 MHz License-free and approved in large parts of Europe
  - UHF 863 - 865 MHz License-free and approved in Europe
  - Operating range up to 80m
- Microphone**
- Polar pattern: Omnidirectional
  - For further information about this product, please refer to the Data Sheet under "Downloads"
- Package contents**
- 1 x transmitter, 1 x microphone, 1 x windshield, 1 x user manual, 1 x declaration of conformity

### Logistic

EAN / GTIN: 4026397700510  
Weight: 0,35 kg  
Length: 0.29 m  
Width: 0.12 m  
Heigh: 0.07 m

### Technical specifications:

Parallel mode: Max. 9 transmitter

Weight: 210 g

Transmitter

Type:	Bodypack with microphone
Power supply:	3 V DC
Power connection:	Battery/battery pack
Battery:	2 x Mignon (AA) (not included)
Gain:	0 dB -6 dB -12 dB
Range:	Range up to 80m
Frequency band:	UHF 823 - 832 MHz; UHF 863 - 865 MHz
Switching bandwidth:	11 MHz
RF power output:	10 mW (LO); 40 mW (HI)
Modulation:	FM
Frequency selection:	90 Switchable frequencies In 10 groups with up to 10 preset frequencies each
Display type:	OLED display
Control elements:	Transmitter power switch (high-low)
Connections:	Output: Mini XLR (M) 4-pin mounting version
Switch:	On/off/mute switch
Material:	Aluminum
Color:	Black
Dimensions:	Width: 6,6 cm Depth: 2,3 cm Height: 8,4 cm
Weight:	174 g
Microphone	
Type:	Headset microphone
Power supply:	2-10 V DC
Cable length:	1,2 m
Capsule type:	Condenser Size: Ø 5 mm x 6 mm
Polar pattern:	Omnidirectional
Frequency range:	50 - 18000 Hz
Sensitivity:	-47 dB
Impedance:	1800 Ohm
Connector type:	Mini XLR (F) 4-pin
Color:	Skin-colored
Weight:	28 g