

RELACART UT-222 Bodypack with HM-600S Headset

Bodypack transmitter with PLL multifrequency transmitter, 823-832 + 863-865 MHz

Art. No.: 13055231
GTIN: 4026397700510



Features:

- Durable aluminum alloy housing, applicable for touring
- Pilot frequency squelch technology delete wireless RF interference
- 10 groups with 90 fixed frequencies within 11 MHz switching bandwidth
- Easy and error-free synchronization between receiver and transmitter via infrared signal
- Adjustable input gain
- RF output power Hi/Low adjustable
- Lock function for prevents undesired changes to settings
- Up to 9 transmitters can be operated in parallel without interference
- transmitter**
- Operating range up to 80m
- UHF 823 - 832 MHz License-free and approved in large parts of Europe
- UHF 863 - 865 MHz License-free and approved in Europe
- OLED display
- microphone**
- Polar pattern: Omnidirectional
- For further information about this product, please refer to the Data Sheet under "Downloads"

Logistic

EAN / GTIN: 4026397700510
Weight: 0,35 kg
Length: 0.29 m
Width: 0.12 m
Heigh: 0.07 m

Technical specifications:

| | |
|----------------|--------------------------|
| Parallel mode: | Max. 9 transmitter |
| Weight: | 0.21 kg |
| Type: | Bodypack with microphone |
| Power supply: | 3V DC |

| | |
|----------------------|--|
| Power connection: | Battery/battery pack |
| Battery: | 2 x Mignon (AA) (not included) |
| Gain: | 0 dB -6 dB -12 dB |
| Range: | Range up to 80m |
| Frequency band: | UHF 823 - 832 MHz; UHF 863 - 865 MHz |
| Switching bandwidth: | 11 MHz |
| RF power output: | UHF 823 - 832 MHz: 10 mW (LO); 40 mW (HI); UHF 863 - 865 MHz: 5 mW (LO); 10 mW (HI) |
| Modulation: | FM |
| Frequency selection: | 90 switchable frequencies In 10 groups with up to 10 preset frequencies each |
| Display type: | OLED display |
| Control elements: | Transmitter power switch (high-low) |
| Connections: | Output: Mini XLR (M) 4-pin mounting version |
| Switch: | On/off/mute switch |
| Material: | Aluminum |
| Color: | Black |
| Dimensions: | Width: 6.6 cm Depth: 2.3 cm Height: 8.4 cm |
| Weight: | 0.174 kg |
| Type: | Headset microphone |
| Power supply: | 2-10V DC |
| Cable length: | 1.2 m |
| Capsule type: | Condenser Size: Ø 5 mm x 6 mm |
| Polar pattern: | Omnidirectional |
| Frequency range: | 50 - 18000 Hz |
| Sensitivity: | -47 dB |
| Impedance: | 1800 Ohm |
| Connector type: | Mini XLR (F) 4-pin |
| Color: | Skin-colored |
| Weight: | 0.028 kg |

Scope of delivery:

- 1 x transmitter
- 1 x microphone
- 1 x windshield
- 1 x user manual
- 1 x declaration of conformity