

## PSSO PXS TWO 2-channel True Diversity Receiver 640-690 MHz

License-free true diversity wireless receiver with auto scan, 3-band EQ & TFT color displays

Art. No.: 13063504

GTIN: 4026397744002



### Features:

- Professional multifrequency wireless receiver with true diversity reception for stage use
- High-grade components and intelligent features ensure best performance and high reliability
- Ideal for large multi-channel systems
- Automatic frequency setup
- Spectrum analysis to identify interference frequencies
- Multifunctional jogdial for menu settings
- 2 detachable BNC antennas allow for use with external antenna divider
- (19") 48.3 cm rack installation possible 1 U
- Operating range up to 200m
- Up to 28 transmitters can be operated in parallel without interference
- Multicolor TFT display
- Charge status indicator

### Logistic

EAN / GTIN: 4026397744002

Weight: 3,50 kg

Length: 0.54 m

Width: 0.41 m

Height: 0.07 m

### Technical specifications:

Type:	Receiver
Power supply:	100-240 V AC, 50/60 Hz 12V DC 1500 mA
Power consumption:	6 W
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) power supply cord with AC adapter (provided)

Number of channels:	2
Frequency range:	30 - 19000 Hz
S/N ratio:	>112 dB
THD:	<0.5 % at 1 kHz
Range:	Range up to 200m
Frequency band:	UHF 640 - 690 MHz
Diversity:	True diversity
Frequency stability:	± 0.001 %
Parallel mode:	Max. 28 transmitter
Frequency selection:	Frequencies automatically scannable
Housing color:	Black
Display type:	Multicolor TFT display
Display:	Frequency , group , channel , charge status indicator; RF signal level , AF audio level , antenna A/B , Mute
Control elements:	Power switch, encoder, exit, menu, sync button
Connections:	Input: antenna via 2 x BNC (F) 11.54 V Output: antenna via 2 x BNC (F) Output: microphone via 2 x 6.3 mm plug (unbal.) Output: microphone via 2 x 3-pin XLR (M) mounting version Output: USB C (W) mounting version 5 V
Equalizer:	3-band tone control
USB port:	2 x type C
Material:	Metal
Mounting dimensions:	48.2 cm x 26 cm x 4.55 cm
Housing design:	(19") 48.3 cm rack installation possible 1 U
Dimensions:	Width: 48.2 cm Depth: 27.4 cm Height: 4.55 cm
Weight:	2.88 kg
Dimensions:	Length: 100 cm
Dimensions:	Length: 100 cm
Dimensions:	Length: 53 cm

### Scope of delivery:

1 x receiver  
2 x antenna  
1 x external mains adapter  
4 x foot  
2 x USB cable  
2 x jack cable  
2 x BNC cable