

# **OMNITRONIC AIRSIS 2.4G Wireless XLR Kit (mic/line)**

Wireless XLR audio system for dynamic microphones and line signals, 2.4 GHz

**Art. No.: 13072203** GTIN: 4026397744729





**List price: 117.81 €** 

incl. 19% VAT.

#### Features:

- Plug-on system with transmitter and receiver ready to use
- Eliminates troublesome cable runs
- For use with mixers, active speakers and dynamic microphones
- Automatic pairing
- 24 bit/48 kHz for the ultimate sound quality
- Rechargeable lithium batteries
- Several receivers can be coupled with a single transmitter
- LED indicator for monitoring the operating status
- Sample rate: 48 kHz
- Note: The device does not provide phantom power. Therefore, only dynamic microphones and condenser microphones that are battery-operated can be used.
- Operating range up to 30m with line-of-sight
- 2.4 GHz license-free worldwide
- Ultra-low latency

# transmitter

- Cordless, flexible and versatile

# receiver

Cordless, flexible and versatile

#### Package contents

- 1 x transmitter, 1 x receiver, 1 x USB cable, 1 x user manual, 1 x declaration of conformity

## **Technical specifications:**

Type: Audio transmission

### Logistic

EAN / GTIN: 4026397744729

Weight: 0,24 kg Length: 0.15 m Width: 0.14 m Heigth: 0.04 m

Protection class:	Protection class III
Power connection:	Mains input via USB C (W) mounting version power supply cord for USB A mains connection (provided)
Frequency range:	20 - 20000 Hz
THD:	Mic/line <0,02 % at 1 kHz
Range:	Range up to 30m with line-of-sight
Frequency band:	2.4 GHz
Latency:	5,8 ms
Housing color:	Black matte
Sample rate:	48 kHz
Converter:	24 bit
Material:	Plastic
Weight:	0,14 kg
Transmitter	
Power connection:	Battery/battery pack built-in
Battery pack type:	1 x lithium ion 3,7 V, 600 mAh, 2,22 Wh
Control elements:	Power switch, Input sensitivity switch
Status LED:	Power, Mute, charge status indicator, pairing
Connections:	Input: mic/line via 1 x 3-pin XLR (F) mounting version
Input channels:	1 x mono with mic-line switch
USB port:	1 x type C
USB port: Dimensions:	1 x type C Length: 10,7 cm
- <u></u>	Length: 10,7 cm Width: 3,0 cm
Dimensions:	Length: 10,7 cm Width: 3,0 cm Depth: 2,2 cm
Dimensions:  Weight:	Length: 10,7 cm Width: 3,0 cm
Dimensions:  Weight:  Receiver	Length: 10,7 cm Width: 3,0 cm Depth: 2,2 cm 0,047 kg
Dimensions:  Weight:  Receiver  Power connection:	Length: 10,7 cm Width: 3,0 cm Depth: 2,2 cm 0,047 kg  Battery/battery pack built-in
Dimensions:  Weight:  Receiver  Power connection:  Battery pack type:	Length: 10,7 cm Width: 3,0 cm Depth: 2,2 cm 0,047 kg  Battery/battery pack built-in 1 x lithium ion 3,7 V, 800 mAh, 2,96 Wh
Dimensions:  Weight:  Receiver  Power connection:	Length: 10,7 cm Width: 3,0 cm Depth: 2,2 cm 0,047 kg  Battery/battery pack built-in
Dimensions:  Weight:  Receiver  Power connection:  Battery pack type:	Length: 10,7 cm Width: 3,0 cm Depth: 2,2 cm 0,047 kg  Battery/battery pack built-in 1 x lithium ion 3,7 V, 800 mAh, 2,96 Wh
Dimensions:  Weight:  Receiver  Power connection:  Battery pack type:  Control elements:	Length: 10,7 cm Width: 3,0 cm Depth: 2,2 cm 0,047 kg  Battery/battery pack built-in 1 x lithium ion 3,7 V, 800 mAh, 2,96 Wh Power switch
Dimensions:  Weight:  Receiver  Power connection:  Battery pack type:  Control elements:  Status LED:	Length: 10,7 cm Width: 3,0 cm Depth: 2,2 cm 0,047 kg  Battery/battery pack built-in 1 x lithium ion 3,7 V, 800 mAh, 2,96 Wh Power switch Power, Mute, charge status indicator, pairing Output: mic/line via 1 x 3-pin XLR (M) mounting
Dimensions:  Weight:  Receiver  Power connection:  Battery pack type:  Control elements:  Status LED:  Connections:	Length: 10,7 cm Width: 3,0 cm Depth: 2,2 cm  0,047 kg  Battery/battery pack built-in  1 x lithium ion 3,7 V, 800 mAh, 2,96 Wh Power switch  Power, Mute, charge status indicator, pairing  Output: mic/line via 1 x 3-pin XLR (M) mounting version  1 x type C  Length: 10,7 cm
Dimensions:  Weight:  Receiver  Power connection:  Battery pack type:  Control elements:  Status LED:  Connections:	Length: 10,7 cm Width: 3,0 cm Depth: 2,2 cm 0,047 kg  Battery/battery pack built-in 1 x lithium ion 3,7 V, 800 mAh, 2,96 Wh Power switch Power, Mute, charge status indicator, pairing Output: mic/line via 1 x 3-pin XLR (M) mounting version 1 x type C Length: 10,7 cm Width: 3,0 cm
Dimensions:  Weight:  Receiver  Power connection:  Battery pack type:  Control elements:  Status LED:  Connections:  USB port:  Dimensions:	Length: 10,7 cm Width: 3,0 cm Depth: 2,2 cm  0,047 kg  Battery/battery pack built-in  1 x lithium ion 3,7 V, 800 mAh, 2,96 Wh  Power switch  Power, Mute, charge status indicator, pairing  Output: mic/line via 1 x 3-pin XLR (M) mounting version  1 x type C  Length: 10,7 cm  Width: 3,0 cm  Depth: 2,2 cm
Dimensions:  Weight:  Receiver  Power connection:  Battery pack type:  Control elements:  Status LED:  Connections:  USB port:  Dimensions:	Length: 10,7 cm Width: 3,0 cm Depth: 2,2 cm 0,047 kg  Battery/battery pack built-in 1 x lithium ion 3,7 V, 800 mAh, 2,96 Wh Power switch Power, Mute, charge status indicator, pairing Output: mic/line via 1 x 3-pin XLR (M) mounting version 1 x type C Length: 10,7 cm Width: 3,0 cm
Dimensions:  Weight:  Receiver  Power connection:  Battery pack type:  Control elements:  Status LED:  Connections:  USB port:  Dimensions:  Weight:  USB cable	Length: 10,7 cm Width: 3,0 cm Depth: 2,2 cm 0,047 kg  Battery/battery pack built-in 1 x lithium ion 3,7 V, 800 mAh, 2,96 Wh Power switch Power, Mute, charge status indicator, pairing Output: mic/line via 1 x 3-pin XLR (M) mounting version 1 x type C Length: 10,7 cm Width: 3,0 cm Depth: 2,2 cm 0,044 kg
Dimensions:  Weight:  Receiver  Power connection:  Battery pack type:  Control elements:  Status LED:  Connections:  USB port:  Dimensions:  Weight:  USB cable  Cable length:	Length: 10,7 cm Width: 3,0 cm Depth: 2,2 cm  0,047 kg  Battery/battery pack built-in  1 x lithium ion 3,7 V, 800 mAh, 2,96 Wh  Power switch  Power, Mute, charge status indicator, pairing  Output: mic/line via 1 x 3-pin XLR (M) mounting version  1 x type C  Length: 10,7 cm Width: 3,0 cm Depth: 2,2 cm  0,044 kg
Dimensions:  Weight:  Receiver  Power connection:  Battery pack type:  Control elements:  Status LED:  Connections:  USB port:  Dimensions:  Weight:  USB cable  Cable length:  Plug A:	Length: 10,7 cm Width: 3,0 cm Depth: 2,2 cm  0,047 kg  Battery/battery pack built-in  1 x lithium ion 3,7 V, 800 mAh, 2,96 Wh  Power switch  Power, Mute, charge status indicator, pairing  Output: mic/line via 1 x 3-pin XLR (M) mounting version  1 x type C  Length: 10,7 cm Width: 3,0 cm Depth: 2,2 cm  0,044 kg  0,5 m  1 x USB A (M)
Dimensions:  Weight:  Receiver  Power connection:  Battery pack type:  Control elements:  Status LED:  Connections:  USB port:  Dimensions:  Weight:  USB cable  Cable length:	Length: 10,7 cm Width: 3,0 cm Depth: 2,2 cm  0,047 kg  Battery/battery pack built-in  1 x lithium ion 3,7 V, 800 mAh, 2,96 Wh  Power switch  Power, Mute, charge status indicator, pairing  Output: mic/line via 1 x 3-pin XLR (M) mounting version  1 x type C  Length: 10,7 cm Width: 3,0 cm Depth: 2,2 cm  0,044 kg