

OMNITRONIC WMR-2M UHF Receiver, mono

Wireless mono audio transmission system, 823-832 MHz + 863-865 MHz

Art. No.: 13072228

GTIN: 4026397665345



Features:

- Wireless audio transmission system with UHF PLL technology
- For wireless transmission of audio line and microphone signals with one transmitter and one or more receivers
- Compatible with wireless modules and microphones of the MOM and DAD series
- 16 channels selectable
- Audio line output and earphone connection via 3.5 mm jack
- Supports operation and simultaneous charging
- Robust metal fixing clip
- WM-2M camera tripod optional
- Battery pack tool-free replacement
- Integrated automatic charging of the battery and status indicator
- Powered by a battery/battery pack
- Operating range up to 50m
- UHF 823 - 832 MHz License-free and approved in large parts of Europe
- UHF 863 - 865 MHz License-free and approved in Europe
- Up to 4 transmitters can be operated in parallel without interference

Logistic

EAN / GTIN: 4026397665345

Weight: 0,21 kg

Length: 0.21 m

Width: 0.09 m

Height: 0.07 m

Technical specifications:

Type: Audio transmission

Power supply: 3V DC

Or

5V DC

Power connection:	Battery/battery pack Mains input via micro USB (F) mounting version power supply cord for USB A mains connection (provided)
Battery:	2 x Mignon (AA) (not included)
S/N ratio:	>80 dB
Range:	Range up to 50m
Frequency band:	UHF 823 - 832 MHz; UHF 863 - 865 MHz
Frequency stability:	± 0.01 %
Parallel mode:	Max. 4 transmitter
Modulation:	FM
Frequency selection:	16 switchable frequencies
Pilot frequency:	32.768 kHz
Control elements:	, frequency selector switch, level control
Status LED:	Power, signal
Connections:	Output: line via 1 x 3.5 mm jack (mono) mounting version 0.75 V Output: headphones via 1 x 3.5 mm jack (mono) mounting version 1 V
Switch:	On/off switch
Material:	Plastic
Color:	Black
Dimensions:	Width: 6.7 cm Depth: 3.0 cm Height: 11.2 cm
Weight:	0.13 kg
Weight:	0.08 kg

Scope of delivery:

- 1 x receiver
- 1 x jack cable
- 1 x USB cable
- 1 x adapter
- 1 x user manual
- 1 x declaration of conformity